



PVC Cut Edge Sealant

**THE RUSCOE
COMPANY**
Adhesives &
Sealants

Description:

Rusco PVC Cut Edge Sealant is a translucent polymeric cut edge sealant specifically designed for superior weatherability and adhesion to PVC roofing membrane..

Advantages:

- Excellent U.V. resistance
- High Adhesion to PVC membrane
- Excellent wet out
- Hydrolytically stable
- Water resistant
- Excellent cold crack resistance

FLAMMABILITY: RED LABEL- EXTREMELY FLAMMABLE

Application Instructions:

The membrane must be clean, dry and free of debris. Apply a 1/8 inch bead of Ruscoe PVC Cut Edge Sealant from a plastic squeeze bottle to the cut edge of the membrane. Allow sealant to dry to a tack-free state prior to inclement weather.

NOTE: The shelf life for an unopened container of this adhesive is one year from date of manufacture.

Physical Properties:

Color:	Translucent
Viscosity:	540-940 cps
Solids:	15-20%
Weight /Gallon	7.8lbs./gal
Application	Squeeze Bottle
VOC Content	754g/lor81.7%
Flash Point (for component)	6° F (-14° C) TCC
Tack Free Time	2 Hours
Cure Time	24 Hours
Shelf Life	One Year, unopened

Attention:

Empty Container remains hazardous until all flammable vapors, which may explode upon ignition, are gone from residue and container. Observe all labeled hazard precautions. Do not cut, puncture, or weld while hazard exists. Do not reuse empty container. Dispose of according to all federal, state and local regulations.

Legal: For your information

All statements, technical information and recommendations contained herein are based on tests believed to be reliable, but the accuracy or completeness is not guaranteed, and the following is made in lieu of all warranties expressed or implied. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of, or the inability to use the product. Before production, user shall determine the suitability of the product for their intended use and assumes all risk and liability in connection with and production.

The Ruscoe Company

P.O. Box 3858, Akron, Ohio 44314-0858 sales@ruscoe.com

485 Kenmore Blvd., Akron, Ohio 44301 • 330-253-8148 • 800-293-8148 • Fax: 330-253-2933