

TECHNICAL DATA SHEET



PAN-L-BOND FIXTURE ADHESIVE

DESCRIPTION

A professional strength adhesive recommended for bonding high stress construction applications. Pan-L-Bond offers excellent water resistance and remains permanently flexible.

SUGGESTED USES

Pan-L-Bond is recommended for bonding high stress construction applications including sub-flooring, stair treads and risers, wet, frozen, and treated lumber, metal, brick, concrete, ceramics and fiberglass.



Product Benefits

- High solids content provides excellent gap filling properties.
- Extremely versatile, bonds most common building materials
- Easily cleaned up with mineral spirits

SURFACE PREPARATION AND APPLICATION

Bonding surfaces must be free of moisture, oils, dirt and other contaminants.

Pan-L-Bond Fixture Adhesive is available in 4-ounce tubes allowing reach into tight spaces. Pan-L-Bond should not be used to bond polystyrene foam.

STORAGE AND SHELF LIFE

Pan-L-Bond Fixture Adhesive should be stored in an unopened container at 77°F. for no longer than 1 year. Rotate stock regularly.

HEALTH AND SAFETY

Health and safety data sheets available upon request at The Ruscoe Company. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn.

CLEANING

For cleanup use Acetone.

TYPICAL PROPERTIES

Color	Tan
Solids, by Weight %	65%
Viscosity, Brookfield, Test Result, CPS (#7 @20 rpm)	130,000
Pounds Per Gallon @25°C (77°F)	9.2
Solvents	Ketone, Aromatic, Aliphatic
Flash point	0°F
Shelf Life	12 Months

All statements, technical information and recommendations contained herein are based on tests believed to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties expressed or implied. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of, or the inability to use the product. Before using, user shall determine the suitability of the product for their intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing many are not changed except by an agreement signed by officers of seller or manufacturer.