

TECHNICAL DATA SHEET



PERMANENT SEALER - SEAM SEALER

DESCRIPTION

Ruscoes Permanent Sealer - Seam Sealer is recommended for sealing openings less than 1/8 inch.

SUGGESTED USES

Seam Sealer can be used as an effective sealant against water, chemicals, and dirt for sealing seams in gutters, downspouts, roof and chimney flashings, animal feeders and troughs, wood, concrete, ceramic, brick, metal, stone, masonry, marble, and glass.

Ruscoes Seam Sealers are recommended for sealing horizontal seams only.



Product Benefits

- **Aluminum fortified adhesive formula.**
- **Excellent adhesion.**
- **Excellent exterior durability.**
- **Can be applied at low temperatures.**
- **Requires no primer.**
- **Good adhesion to either porous or non-porous substrates – including glass.**
- **Weatherproof – skins over to form a protective seal.**

METHOD OF APPLICATION

Ruscoes Permanent Sealer - Seam Sealers are packaged in 4-ounce metal tubes to aid in more detailed applications.

PERMANENT SEALER NITRILE RUBBER SEALANTS

Seam Sealers, Self-Leveling Sealant and Non-Sag Sealant are members of a special family of sealants based upon an aluminum fortified formula, they incorporate the protective and elastic qualities of synthetic elastomers. In addition to aluminum, Seam Sealer is also available in White and Brown.

HEALTH AND SAFETY

Health and safety data sheets available upon request at The Ruscoe Company. Ruscoe nitrile rubber sealants contain ingredients which could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn.

TYPICAL PROPERTIES

	Aluminum	White	Brown
Color	Aluminum	White	Brown
Base Polymer	Nitrile Rubber	Nitrile Rubber	Nitrile Rubber
Solids, by Weight %	44	50	49
Flash Point, (TCC), °F	<0	<0	<0
Solvent Formulation	Ketone, Aromatic, Ester	Ketone, Aromatic, Ester	Ketone, Aromatic, Ester
Viscosity, Brookfield, Test Result, CPS (#7 @20RPM)	50,000	60,000	68,000
Pounds Per Gallon @25°C (77°F)	8.0	9.1	8.576
Application Temperature, °F	40 – 100	40 – 100	40 – 100
Clean Up	Acetone	Acetone	Acetone
VOC grams/liter	90	90	90

All statements, technical information and recommendations contained herein are based on tests believed to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties expressed or implied. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of, or the inability to use the product. Before using, user shall determine the suitability of the product for their intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing many are not changed except by an agreement signed by officers of seller or manufacturer.