



**THE RUSCOE
COMPANY**
Adhesives &
Sealants

Pan-L-Bond Construction Adhesive

PRODUCT DESCRIPTION:

Pan-L-Bond Construction Adhesive is a professional strength adhesive recommended for bonding high stress construction applications including: sub-flooring, stair treads and risers, wet, frozen and treated lumber, metal, brick, concrete, ceramics, and fiberglass. Pan-L-Bond Construction Adhesive offers excellent water resistance and remains permanently flexible. Pan-L-Bond Construction Adhesive can not be used to bond polystyrene foam.

PRODUCT BENEFITS:

- * High solids content provides excellent gap filling properties
- * Extremely versatile, bonds most common building materials
- * Easily cleaned up with mineral spirits
- * Exceed the performance requirements of the American Plywood Association AFG-OI Specification, HUD/FHA of Materials Bulletin #60, ASTM D3498 and ASTM C557

Physical Properties:

COLOR: Light Tan

STATE: Medium-viscosity mastic

BASE POLYMER: Synthetic elastomeric polymer

TOTAL SOLIDS BY WEIGHT: 65%

VISCOSITY: 130,000 cps

SOLVENTS: Ketone, Aliphatic, Aromatic

FLASH POINT: Less than 0° F

FREEZE/THAW STABILITY: Stable

WEIGHT PER GALLON: 9.2 lbs.

CALCULATED VOC: (less exempt solvent): 282g/l

Insulation Clip Hanger Test That Was Developed Performed By The Ruscoe Company

Perforated base insulation hangers were bonded to a zinc coated steel panel. The adhesive was allowed to cure for six to seven days at room temperature. A one pound weight was then attached and suspended from the end of the insulation clip. The panels were then placed in an oven at 200° F. for two hours. The temperature was increased at 25° F. intervals after each two hour period. Release temperature exceeded 250° F.

Recommended Storage Life

Pan-L-Bond Construction Adhesive should be stored in an unopened container at 77° F. for no longer than one year. Rotate stock regularly.

Notice to Customers

Because we do not know the particular use for which this product may be purchased nor how it may be applied, we cannot guarantee its suitability for your purpose. However, we will refund the purchase price if this product is defective. This shall be the customer's only remedy. We cannot assume any obligation or liability for the results of customer use or a customer's liability to use this product

The Ruscoe Company

P.O. Box 3858, Akron, Ohio 44314-0858 sales@ruscoe.com

485 Kenmore Blvd., Akron, Ohio 44301 • 330-253-8148 • 800-293-8148 • Fax: 330-253-2933