

# TECHNICAL DATA SHEET



## 11109 PREMIUM BUTYL SEALANT

### DESCRIPTION

Ruscoe's Butyl Lap Sealant is a one-part, solvent release butyl rubber flexible sealant designed to provide excellent weathering properties. This is an excellent exterior butyl compound formulated for applications requiring a long life.

### SUGGESTED USES

It is designed for sealing EPDM rubber, TPO, fiberglass, wood, aluminum, steel or masonry.



### PRODUCT BENEFITS

- Easy to apply.
- Remains permanently flexible
- Non-staining
- Adheres to a variety of surfaces without primer.

### METHOD OF APPLICATION

All surfaces must be clean, dry and free of all loose materials. Apply with a standard caulking gun.

Cut the nozzle to desired bead size and puncture the inner seal. Apply at a 45° angle using constant pressure. For ease of gunning, use at room temperature. Tool or joint surfaces for sealing before material skins. Support tooled or joined surfaces for 8 hours minimum. Use Mineral Spirits or VM&P Naphtha to remove excess material before skin forms.

### STORAGE

Store in original packaging.

### HEALTH AND SAFETY

Health and safety data sheets available upon request at The Ruscoe Company.

### LIMITATIONS

All surfaces to be sealed or bonded must be clean and dry and free from contaminants. Ruscoe Premium Butyl Sealant is NOT recommended for use in window glazing applications or hidden joint details, which require a non-skinning, non-hardening sealant.

### CLEAN UP

Clean up with VM&P Naphtha or Mineral Spirits.

### TYPICAL PROPERTIES

|                                |              |
|--------------------------------|--------------|
| Color                          | White        |
| Solids, by Weight %            | 80-.5% min   |
| Solvent Formulation            | VM&P Naphtha |
| V.O.C. Content (calculated)    | 240 g/L      |
| Pounds Per Gallon @77°F (25°C) | 10.23        |

All statements, technical information and recommendations contained herein are based on tests believed to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties express or implied. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of, or the inability to use the product. Before using, user shall determine the suitability of the product for their intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing many are not changed except by an agreement signed by officers of seller or manufacturer.