



SECTION 1: IDENTIFICATION

- 1.1 GHS Product identifier:** DH-7-158
Other means of identification:
Not applicable (N/A)
- 1.2 Recommended use of the chemical and restrictions on use:**
Relevant uses: Adhesive. For professional users/industrial user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:**
The Ruscoe Company
485 Kenmore Blvd
44301 Akron - United States
Phone: 330-253-8148
Sales@Ruscoe.com; SDS@Ruscoe.com
www.ruscoe.com
- 1.4 Emergency phone number:** Chemtrec 1-800-424-9300

SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
29 CFR 1910.1200:
Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.
Eye Irrit. 2A: Eye irritation, Category 2A, H319
Flam. Liq. 2: Flammable liquids, Category 2, H225
Muta. 2: Germ cell mutagenicity, Category 2, H341
Skin Irrit. 2: Skin irritation, Category 2, H315
STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

29 CFR 1910.1200:

Danger



Hazard statements:

Eye Irrit. 2A: H319 - Causes serious eye irritation.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Muta. 2: H341 - Suspected of causing genetic defects.
Skin Irrit. 2: H315 - Causes skin irritation.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313: IF exposed or concerned: Get medical advice/attention.
P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.
P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Substances that contribute to the classification

Methyl Ethyl Ketone (CAS: 78-93-3); PHENOL (CAS: 108-95-2)

- CONTINUED ON NEXT PAGE -



SECTION 2: HAZARD(S) IDENTIFICATION (continued)

Additional labeling:



WARNING

This product can expose you to chemicals including methanol, 4-vinylcyclohexene, 1,3-butadiene, which is [are] known to the State of California to cause cancer, and Vinyl chloride, acetaldehyde, Formaldehyde, 4-vinylcyclohexene, Acrylonitrile, 1,3-butadiene, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

2.3 Hazards not otherwise classified (HNOC):

Not applicable (N/A)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Non-applicable

3.2 Mixtures:

Chemical description: Mixture composed of additives and resins in solvents

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 78-93-3	Methyl Ethyl Ketone Eye Irrit. 2A: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	75 - <100 %
CAS: 108-95-2	phenol Acute Tox. 3: H301+H311+H331; Flam. Liq. 4: H227; Muta. 2: H341; Skin Corr. 1B: H314; STOT RE 2: H373 - Danger	1 - <2.5 %
CAS: 95-48-7	Ortho-cresol Acute Tox. 3: H301+H311; Skin Corr. 1B: H314 - Danger	<1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

- CONTINUED ON NEXT PAGE -



SECTION 4: FIRST-AID MEASURES (continued)

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Not available

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and materials for containment and cleaning up:

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

- CONTINUED ON NEXT PAGE -



DH-7-158



SECTION 7: HANDLING AND STORAGE (continued)

Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Because the product is a flammable liquid, storage should meet the requirement of 29 CFR 1910.106, Flammable and Combustible Liquids Code. Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems and with the minimum requirements for protecting the security and health of workers. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 41 °F

Maximum Temp.: 90 °F

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
	8-hour TWA PEL	200 ppm	590 mg/m ³
Methyl Ethyl Ketone CAS: 78-93-3	Ceiling Values - TWA PEL		
methanol ⁽¹⁾ CAS: 67-56-1	8-hour TWA PEL	200 ppm	260 mg/m ³
	Ceiling Values - TWA PEL		
Vinyl chloride CAS: 75-01-4	8-hour TWA PEL	1 ppm	
	Ceiling Values - TWA PEL	5 ppm	
acetaldehyde CAS: 75-07-0	8-hour TWA PEL	200 ppm	360 mg/m ³
	Ceiling Values - TWA PEL		
phenol ⁽¹⁾ CAS: 108-95-2	8-hour TWA PEL	5 ppm	19 mg/m ³
	Ceiling Values - TWA PEL		
Ortho-cresol CAS: 95-48-7	8-hour TWA PEL	55 ppm	22 mg/m ³
	Ceiling Values - TWA PEL		
Formaldehyde ⁽²⁾ CAS: 50-00-0	8-hour TWA PEL	0.75 ppm	
	Ceiling Values - TWA PEL	2 ppm	
Acrylonitrile ⁽³⁾ CAS: 107-13-1	8-hour TWA PEL	1 ppm	
	Ceiling Values - TWA PEL	10 ppm	
1,3-butadiene	8-hour TWA PEL	1 ppm	

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
	Ceiling Values - TWA		
CAS: 106-99-0	PEL		

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		
	TLV-TWA		
Methyl Ethyl Ketone CAS: 78-93-3	TLV-TWA	50 ppm	
	TLV-STEL	100 ppm	
methanol ⁽¹⁾ CAS: 67-56-1	TLV-TWA	200 ppm	
	TLV-STEL	250 ppm	
vinyl acetate CAS: 108-05-4	TLV-TWA	10 ppm	
	TLV-STEL	15 ppm	
Vinyl chloride CAS: 75-01-4	TLV-TWA	1 ppm	
	TLV-STEL		
phenol ⁽¹⁾ CAS: 108-95-2	TLV-TWA	5 ppm	
	TLV-STEL		
Ortho-cresol CAS: 95-48-7	TLV-TWA		10 mg/m ³
	TLV-STEL		
Formaldehyde ⁽²⁾ CAS: 50-00-0	TLV-TWA	0.1 ppm	
	TLV-STEL	0.3 ppm	
4-vinylcyclohexene CAS: 100-40-3	TLV-TWA	0.1 ppm	
	TLV-STEL		
Acrylonitrile ⁽³⁾ CAS: 107-13-1	TLV-TWA	2 ppm	
	TLV-STEL		
1,3-butadiene CAS: 106-99-0	TLV-TWA	2 ppm	
	TLV-STEL		

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occupational exposure limits		
methanol ⁽¹⁾ CAS: 67-56-1	PEL	200 ppm	260 mg/m ³
	STEL	250 ppm	325 mg/m ³
vinyl acetate CAS: 108-05-4	PEL	10 ppm	30 mg/m ³
	STEL	15 ppm	45 mg/m ³
Vinyl chloride CAS: 75-01-4	PEL	1 ppm	
	STEL		
acetaldehyde CAS: 75-07-0	PEL	25 ppm	45 mg/m ³
	STEL	25 ppm	45 mg/m ³
phenol ⁽¹⁾ CAS: 108-95-2	PEL	5 ppm	19 mg/m ³
	STEL		
Ortho-cresol CAS: 95-48-7	PEL	5 ppm	22 mg/m ³
	STEL		
Formaldehyde ⁽²⁾ CAS: 50-00-0	PEL	0.75 ppm	
	STEL	2 ppm	
4-vinylcyclohexene CAS: 100-40-3	PEL	0.1 ppm	0.4 mg/m ³
	STEL		
Acrylonitrile ⁽³⁾ CAS: 107-13-1	PEL	2 ppm	4.5 mg/m ³
	STEL		
1,3-butadiene CAS: 106-99-0	PEL	1 ppm	2.2 mg/m ³
	STEL	5 ppm	11 mg/m ³

⁽¹⁾ Skin

⁽²⁾ Dermal sensitisation

⁽³⁾ Skin, Dermal sensitisation

Biological limit values:

Biological Exposure Indices (BEIs®) - ACGIH

Identification	BEIs®	Determinant	Sampling Time
Methyl Ethyl Ketone CAS: 78-93-3	2 mg/L	Methyl ethyl ketone in urine	End of shift
methanol CAS: 67-56-1	15 mg/L	Methanol in urine	End of shift
phenol CAS: 108-95-2	250 mg/L	Phenol in urine	End of shift

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Biological Exposure Indices (BEIs®) - ACGIH


Identification	BEIs®	Determinant	Sampling Time
1,3-butadiene CAS: 106-99-0	2.5 mg/L	1,2 Dihydroxy-4-(N-acetylcysteinyl)-butane in urine	End of shift

8.2 Appropriate engineering controls:


A.- Individual protection measures, such as personal protective equipment

Always provide effective general and, when necessary, local exhaust ventilation to maintain the ambient workplace atmosphere below the exposure limits.. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection


Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR)

C.- Specific protection for the hands



Pictogram	PPE	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

E.- Bodily protection

Pictogram	PPE	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 68 °F:	Liquid
Appearance:	Not available
Color:	Not available
Odor:	Not available
Odour threshold:	Not available *

Volatility:

Boiling point at atmospheric pressure:	177 °F
Vapour pressure at 74 °F:	11302 Pa
Vapour pressure at 122 °F:	35344.62 Pa (35.34 kPa)
Evaporation rate at 74 °F:	Not available *

Product description:

Density at 74 °F:	853.2 kg/m ³
Relative density at 74 °F:	0.853
Dynamic viscosity at 74 °F:	Not available *
Kinematic viscosity at 74 °F:	Not available *
Kinematic viscosity at 104 °F:	Not available *
Concentration:	Not available *
pH:	Not available *
Vapour density at 74 °F:	Not available *
Partition coefficient n-octanol/water 74 °F:	Not available *
Solubility in water at 74 °F:	Not available *
Solubility properties:	Not available *
Decomposition temperature:	Not available *
Melting point/freezing point:	Not available *

Flammability:

Flash Point:	21 °F
Flammability (solid, gas):	Not available *
Autoignition temperature:	365 °F
Lower flammability limit:	Not available
Upper flammability limit:	Not available

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not available *
Oxidising properties:	Not available *

*Not available due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Corrosive to metals:	Not available *
Heat of combustion:	Not available *
Aerosols-total percentage (by mass) of flammable components:	Not available *
Other safety characteristics:	
Surface tension at 74 °F:	Not available *
Refraction index:	Not available *

*Not available due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: vinyl acetate (2B); Vinyl chloride (1); acetaldehyde (2B); phenol (3); Formaldehyde (1); 4-vinylcyclohexene (2B); Acrylonitrile (2B); 1,3-butadiene (1)
 - Mutagenicity: Exposure to this product can cause genetic modifications. For more specific information on the possible health effects see section 2.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitizing effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) - single exposure:
- Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- G- Specific target organ toxicity (STOT)-repeated exposure:
- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
 - Skin: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:
- Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not applicable (N/A)

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Methyl Ethyl Ketone CAS: 78-93-3	4000 mg/kg	6400 mg/kg	Rat
		23.5 mg/L (4 h)	Rabbit
			Rat
phenol CAS: 108-95-2	100 mg/kg (ATEi)	630 mg/kg (ATEi)	Rat
		3 mg/L (ATEi)	Rabbit
Ortho-cresol CAS: 95-48-7	120 mg/kg (ATEi)	300 mg/kg (ATEi)	Rat
		>5 mg/L	Rat

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	2309.29 mg/kg (Calculation method)	0 %
Dermal	19484.13 mg/kg (Calculation method)	0 %
Inhalation	157.73 mg/L (4 h) (Calculation method)	0 %

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available
Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect.
For more information see section 3.

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
Methyl Ethyl Ketone CAS: 78-93-3	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
phenol CAS: 108-95-2	LC50	14 mg/L (96 h)	Leuciscus idus	Fish
	EC50	12 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	370 mg/L (96 h)	Chlorella vulgaris	Algae
Ortho-cresol CAS: 95-48-7	LC50	14 mg/L (96 h)	Pimephales promelas	Fish
	EC50	Not applicable (N/A)		
	EC50	Not applicable (N/A)		

Chronic toxicity:

Identification	Concentration		Species	Genus
phenol CAS: 108-95-2	NOEC	0.077 mg/L	Cirrhina mrigala	Fish
	NOEC	0.16 mg/L	Daphnia magna	Crustacean
Ortho-cresol CAS: 95-48-7	NOEC	1.35 mg/L	Pimephales promelas	Fish
	NOEC	1 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Methyl Ethyl Ketone CAS: 78-93-3	BOD5	2.03 g O2/g	Concentration	Not applicable (N/A)
	COD	2.31 g O2/g	Period	20 days
	BOD5/COD	0.88	% Biodegradable	89 %
phenol CAS: 108-95-2	BOD5	1.68 g O2/g	Concentration	100 mg/L
	COD	2.33 g O2/g	Period	14 days
	BOD5/COD	0.72	% Biodegradable	85 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
Methyl Ethyl Ketone CAS: 78-93-3	BCF	3
	Pow Log	0.29
	Potential	Low
phenol CAS: 108-95-2	BCF	17
	Pow Log	1.48
	Potential	Low
Ortho-cresol CAS: 95-48-7	BCF	6
	Pow Log	1.95
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Methyl Ethyl Ketone CAS: 78-93-3	Koc	30	Henry	5.77 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.396E-2 N/m (77 °F)	Moist soil	Yes
phenol CAS: 108-95-2	Koc	50	Henry	2.2E-2 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	1.847E-2 N/m (447.82 °F)	Moist soil	Yes
Ortho-cresol CAS: 95-48-7	Koc	1.34	Henry	1.216E-1 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	No
	Surface tension	1.635E-2 N/m (441.9 °F)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Non-applicable

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continued)

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

The next characteristic per RCRA could apply to the unused product if it becomes a waste material: Ignitability. The next EPA hazardous waste number could apply: D001.

IT IS THE RESPONSIBILITY OF THE WASTE GENERATOR TO EVALUATE WHETHER HIS WASTES ARE HAZARDOUS BY CHARACTERISTICS OR LISTING.

Waste management (disposal and evaluation):

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

Regulations related to waste management:

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:



14.1 UN number: UN1133

14.2 UN proper shipping name: ADHESIVES

14.3 Transport hazard class(es): 3

Labels: 3

14.4 Packing group, if applicable: II

14.5 Marine pollutant: No

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable (N/A)

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

- CONTINUED ON NEXT PAGE -



SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN1133
14.2 UN proper shipping name: ADHESIVES
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group, if applicable: II
14.5 Marine pollutant: No
14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises
 Special regulations: Not applicable (N/A)
 EmS Codes: F-E, S-D
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
 Segregation group: Not applicable (N/A)
14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable (N/A)

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



- 14.1 UN number:** UN1133
14.2 UN proper shipping name: ADHESIVES
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group, if applicable: II
14.5 Marine pollutant: No
14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises
 Physico-Chemical properties: see section 9
14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable (N/A)

SECTION 15: REGULATORY INFORMATION

- 15.1 Safety, health and environmental regulations specific for the product in question:**

- CONTINUED ON NEXT PAGE -



SECTION 15: REGULATORY INFORMATION (continued)

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *Methyl Ethyl Ketone (78-93-3)*; *methanol (67-56-1)*; *vinyl acetate (108-05-4)*; *Vinyl chloride (75-01-4)*; *acetaldehyde (75-07-0)*; *phenol (108-95-2)*; *Ortho-cresol (95-48-7)*; *Formaldehyde (50-00-0)*; *4-vinylcyclohexene (100-40-3)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: *methanol (67-56-1)*; *4-vinylcyclohexene (100-40-3)*; *1,3-butadiene (106-99-0)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: *Vinyl chloride (75-01-4)*; *acetaldehyde (75-07-0)*; *Formaldehyde (50-00-0)*; *4-vinylcyclohexene (100-40-3)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*
- CANADA-Domestic Substances List (DSL): *Methyl Ethyl Ketone (78-93-3)*; *methanol (67-56-1)*; *vinyl acetate (108-05-4)*; *Vinyl chloride (75-01-4)*; *acetaldehyde (75-07-0)*; *phenol (108-95-2)*; *Ortho-cresol (95-48-7)*; *Formaldehyde (50-00-0)*; *NBR (9003-18-3)*; *4-vinylcyclohexene (100-40-3)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*
- CANADA-Non-Domestic Substances List (NDSL): Not applicable (N/A)
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: *Methyl Ethyl Ketone (78-93-3)* - U159; *methanol (67-56-1)* - U154; *vinyl acetate (108-05-4)* - 5000 lb; *Vinyl chloride (75-01-4)* - U043; *acetaldehyde (75-07-0)* - U001; *phenol (108-95-2)* - U188; *Ortho-cresol (95-48-7)* - 100 lb; *Formaldehyde (50-00-0)* - U122; *Acrylonitrile (107-13-1)* - U009; *1,3-butadiene (106-99-0)* - 10 lb
- Hazardous Air Pollutants (Clean Air Act): *methanol (67-56-1)*; *vinyl acetate (108-05-4)*; *Vinyl chloride (75-01-4)*; *acetaldehyde (75-07-0)*; *phenol (108-95-2)*; *Ortho-cresol (95-48-7)*; *Formaldehyde (50-00-0)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*
- Massachusetts RTK - Substance List: *Methyl Ethyl Ketone (78-93-3)*; *methanol (67-56-1)*; *vinyl acetate (108-05-4)*; *Vinyl chloride (75-01-4)*; *acetaldehyde (75-07-0)*; *phenol (108-95-2)*; *Ortho-cresol (95-48-7)*; *Formaldehyde (50-00-0)*; *4-vinylcyclohexene (100-40-3)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*
- Minnesota - Hazardous substances ERTK: *Methyl Ethyl Ketone (78-93-3)*; *methanol (67-56-1)*; *vinyl acetate (108-05-4)*; *Vinyl chloride (75-01-4)*; *acetaldehyde (75-07-0)*; *phenol (108-95-2)*; *Ortho-cresol (95-48-7)*; *Formaldehyde (50-00-0)*; *4-vinylcyclohexene (100-40-3)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*
- New Jersey Worker and Community Right-to-Know Act: *Methyl Ethyl Ketone (78-93-3)*; *methanol (67-56-1)*; *vinyl acetate (108-05-4)*; *Vinyl chloride (75-01-4)*; *acetaldehyde (75-07-0)*; *phenol (108-95-2)*; *Ortho-cresol (95-48-7)*; *Formaldehyde (50-00-0)*; *4-vinylcyclohexene (100-40-3)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*
- New York RTK - Substance list: *Methyl Ethyl Ketone (78-93-3)*; *methanol (67-56-1)*; *vinyl acetate (108-05-4)*; *Vinyl chloride (75-01-4)*; *acetaldehyde (75-07-0)*; *phenol (108-95-2)*; *Ortho-cresol (95-48-7)*; *Formaldehyde (50-00-0)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*
- NTP (National Toxicology Program): *Vinyl chloride (75-01-4)*; *acetaldehyde (75-07-0)*; *Formaldehyde (50-00-0)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): *Vinyl chloride (75-01-4)*; *Formaldehyde (50-00-0)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*
- Pennsylvania Worker and Community Right-to-Know Law: *Methyl Ethyl Ketone (78-93-3)*; *methanol (67-56-1)*; *vinyl acetate (108-05-4)*; *Vinyl chloride (75-01-4)*; *acetaldehyde (75-07-0)*; *phenol (108-95-2)*; *Ortho-cresol (95-48-7)*; *Formaldehyde (50-00-0)*; *4-vinylcyclohexene (100-40-3)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*
- Rhode Island - Hazardous substances RTK: *Methyl Ethyl Ketone (78-93-3)*; *methanol (67-56-1)*; *vinyl acetate (108-05-4)*; *Vinyl chloride (75-01-4)*; *acetaldehyde (75-07-0)*; *phenol (108-95-2)*; *Ortho-cresol (95-48-7)*; *Formaldehyde (50-00-0)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*
- The Toxic Substances Control Act (TSCA) (USA, Puerto Rico): *Methyl Ethyl Ketone (78-93-3)*; *methanol (67-56-1)*; *vinyl acetate (108-05-4)*; *Vinyl chloride (75-01-4)*; *acetaldehyde (75-07-0)*; *phenol (108-95-2)*; *Ortho-cresol (95-48-7)*; *Formaldehyde (50-00-0)*; *NBR (9003-18-3)*; *4-vinylcyclohexene (100-40-3)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): *methanol (67-56-1)*; *vinyl acetate (108-05-4)*; *Vinyl chloride (75-01-4)*; *acetaldehyde (75-07-0)*; *phenol (108-95-2)*; *Ortho-cresol (95-48-7)*; *Formaldehyde (50-00-0)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Texts of the legislative phrases mentioned in section 2:

- CONTINUED ON NEXT PAGE -



SECTION 16: OTHER INFORMATION (continued)

H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H341: Suspected of causing genetic defects.
H315: Causes skin irritation.
H373: May cause damage to organs through prolonged or repeated exposure.
H225: Highly flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

29 CFR 1910.1200:

Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin.
Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.
Eye Irrit. 2A: H319 - Causes serious eye irritation.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Flam. Liq. 4: H227 - Combustible liquid.
Muta. 2: H341 - Suspected of causing genetic defects.
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Advice related to training:

According to 29 CFR 1910. 1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

Abbreviations and acronyms:

IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
CL50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon
IARC: International Agency for Research on Cancer

Date of compilation: 4/12/2024

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET