# **TECHNICAL DATA SHEET**




# ROOFING MEMBRANE CLEANER V.O.C. EXEMPT

#### **DESCRIPTION AND USES**

Ruscoe V.O.C. Exempt Membrane Cleaner is used to remove dirt, asphalt or other contaminants from PVC, TPO and EPDM membrane to ensure a good weld or bond. It is required when tapes or adhesives are used on the membrane.





# **METHOD OF APPLICATION**

Apply cleaner to a clean, natural fiber rag and remove contaminants by using a scrubbing motion. Ruscoe V.O.C. Exempt Membrane Cleaner is to be used only in wipe cleaning using a wetted rag or similar material. Change rags frequently. Allow the membrane cleaner to dry thoroughly prior to application of tape or adhesives.

#### PRECAUTIONS:

Membranes or flashings that have been exposed to weather or the elements longer than seven days must be cleaned with Ruscoe V.O.C. Exempt Membrane Cleaner prior to welding or bonding. Refer to Safety Data Sheet (SDS) prior to using Ruscoe V.O.C. Exempt Membrane Cleaner.

# STORAGE AND SHELF LIFE

Store in a dry area protected from weather and extreme temperatures.

DO NOT STORE IN DIRECT SUNLIGHT.

Ruscoe V.O.C. Exempt Membrane Cleaner is flammable and must be kept away from heat, sparks and flames. Use only in well-ventilated areas. Close containers after use. May cause possible skin irritation; use chemically resistant gloves when using this product. Keep out of reach of children.

Shelf life is 12 months when stored between 60°F-80°F (16°C-27°C) in unopened containers.

# **HEALTH AND SAFETY**

Health and safety data sheets available upon request at The Ruscoe Company.

### **COVERAGE RATE**

Approximately 400ft²/gal (9.82m²/l).

TYPICAL PROPERTIES	
Solids, by Weight %	0%
Solvent Formulation	Acetone
Flash Point	0°F TCC
Pounds Per Gallon @77°F (25°C)	6.61

All statements, technical information and recommendations contained herein are based on tests believed to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties expresses or implied.
Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nr manufacturer shall be liable

Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nr manufacturer shall be liable for any injury, loss, or damage, direct or consequential, ansing out of the use of, or the inability to use the product. Before using, user shall determine the suitability of the product for their intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing many are not changed except by an agreement signed by officers of seller or manufacturer.