



## MS Joint Sealant Non-Sag, Gray



### SECTION 1: IDENTIFICATION

- 1.1 GHS Product identifier:** MS Joint Sealant Non-Sag, Gray  
**Other means of identification:**  
Not applicable (N/A)
- 1.2 Recommended use of the chemical and restrictions on use:**  
Relevant uses: Adhesive. For professional users/industrial user only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:**  
The Ruscoe Company  
485 Kenmore Blvd  
44301 Akron - United States  
Phone: 330-253-8148  
Sales@Ruscoe.com; SDS@Ruscoe.com  
www.ruscoe.com
- 1.4 Emergency phone number:** Chemtrec 1-800-424-9300

### SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**  
**29 CFR 1910.1200:**  
Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.  
Carc. 2: Carcinogenicity, Category 2, H351  
Eye Irrit. 2A: Eye irritation, Category 2A, H319  
Muta. 2: Germ cell mutagenicity, Category 2, H341  
Repr. 1B: Reproductive toxicity, Category 1B, H360  
Skin Sens. 1B: Sensitisation, skin, Category 1B, H317  
STOT RE 1: Specific target organ toxicity, repeated exposure, Category 1, H372  
STOT SE 1: Specific target organ toxicity — single exposure, Category 1, H370
- 2.2 Label elements:**  
**29 CFR 1910.1200:**  
**Danger**
- 
- Hazard statements:**  
Carc. 2: H351 - Suspected of causing cancer.  
Eye Irrit. 2A: H319 - Causes serious eye irritation.  
Muta. 2: H341 - Suspected of causing genetic defects.  
Repr. 1B: H360 - May damage fertility or the unborn child.  
Skin Sens. 1B: H317 - May cause an allergic skin reaction.  
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.  
STOT SE 1: H370 - Causes damage to organs.
- Precautionary statements:**  
P201: Obtain special instructions before use.  
P260: Do not breathe dust/fume/gas/mist/vapours/spray.  
P264: Wash thoroughly after use.  
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.  
P302+P352: IF ON SKIN: Wash with plenty of soap and water.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313: IF exposed or concerned: Get medical advice/attention.  
P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
- Substances that contribute to the classification**  
Trimethoxyvinylsilane (CAS: 2768-02-7); Dibutyltin oxide (CAS: 818-08-6); CI 77266 (CAS: 1333-86-4)

- CONTINUED ON NEXT PAGE -



## MS Joint Sealant Non-Sag, Gray



### SECTION 2: HAZARD(S) IDENTIFICATION (continued)

#### Additional labeling:



#### WARNING

This product can expose you to chemicals including Di-isononyl phthalate, which is [are] known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### 2.3 Hazards not otherwise classified (HNOC):

Not applicable (N/A)

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances:

Non-applicable

#### 3.2 Mixtures:

**Chemical description:** Mixture composed of additives and resins in solvents

#### Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 2768-02-7	<b>Trimethoxyvinylsilane</b> Acute Tox. 4: H332; Flam. Liq. 3: H226; Skin Sens. 1B: H317 - Warning	2.5 - <10 %
CAS: 818-08-6	<b>Dibutyltin oxide</b> Acute Tox. 4: H302; Eye Dam. 1: H318; Muta. 2: H341; Repr. 1B: H360; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 1: H372; STOT SE 1: H370 - Danger	1 - <2.5 %
CAS: 1333-86-4	<b>Carbon black</b> Carc. 2: H351 - Warning	<1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

### SECTION 4: FIRST-AID MEASURES

#### 4.1 Description of necessary measures:

Request medical assistance immediately, showing the SDS of this product.

##### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

##### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

##### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

##### By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Induce vomiting (ONLY IN CONSCIOUS PEOPLE!) and then ingest large quantities of liquid to dilute the toxin. Keep the person affected at rest.

#### 4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

- CONTINUED ON NEXT PAGE -



## MS Joint Sealant Non-Sag, Gray



### SECTION 4: FIRST-AID MEASURES (continued)

#### 4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Not applicable (N/A)

### SECTION 5: FIRE-FIGHTING MEASURES

#### 5.1 Suitable (and unsuitable) extinguishing media:

##### Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

##### Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

#### 5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

##### Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

##### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

##### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

#### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

#### 6.3 Methods and materials for containment and cleaning up:

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

- CONTINUED ON NEXT PAGE -



**MS Joint Sealant Non-Sag, Gray**



**SECTION 7: HANDLING AND STORAGE (continued)**

**B.- Technical recommendations for the prevention of fires and explosions**

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

**C.- Technical recommendations on general occupational hygiene**

**PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT.** Transfer in fixed places that comply with the necessary security conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to containers of small amounts. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

**D.- Technical recommendations to prevent environmental risks**

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:**

**A.- Technical measures for storage**

Minimum Temp.: 41 °F

Maximum Temp.: 90 °F

**B.- General conditions for storage**

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
Limestone CAS: 1317-65-3	8-hour TWA PEL		5 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
Titanium dioxide CAS: 13463-67-7	8-hour TWA PEL		15 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
Carbon black CAS: 1333-86-4	8-hour TWA PEL		3.5 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
Dibutyltin oxide CAS: 818-08-6	8-hour TWA PEL		0.1 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		
Limestone CAS: 1317-65-3	TLV-TWA		10 mg/m <sup>3</sup>
	TLV-STEL		20 mg/m <sup>3</sup>
Titanium dioxide CAS: 13463-67-7	TLV-TWA		2.5 mg/m <sup>3</sup>
	TLV-STEL		
Carbon black CAS: 1333-86-4	TLV-TWA		3 mg/m <sup>3</sup>
	TLV-STEL		
Dibutyltin oxide CAS: 818-08-6	TLV-TWA		2 mg/m <sup>3</sup>
	TLV-STEL		

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occupational exposure limits		
Calcium Carbonate CAS: 471-34-1	PEL		
	STEL		
Carbon black CAS: 1333-86-4	PEL		3.5 mg/m <sup>3</sup>
	STEL		

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

**CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:**


Identification	Occupational exposure limits	
Dibutyltin oxide CAS: 818-08-6	PEL	2 mg/m <sup>3</sup>
	STEL	

**8.2 Appropriate engineering controls:**


**A.- Individual protection measures, such as personal protective equipment**

Always provide effective general and, when necessary, local exhaust ventilation to maintain the ambient workplace atmosphere below the exposure limits.. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

**B.- Respiratory protection**


Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR)

**C.- Specific protection for the hands**



Pictogram	PPE	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Butyl, Breakthrough time: > 480 min, Thickness: 0.7 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



**D.- Eye and face protection**

Pictogram	PPE	Remarks
 Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

**E.- Bodily protection**

Pictogram	PPE	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer's use limitations and OSHA standard 1910.136 (29CFR)

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

- CONTINUED ON NEXT PAGE -



## MS Joint Sealant Non-Sag, Gray



### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

#### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

##### Appearance:

Physical state at 68 °F:	Liquid
Appearance:	Paste
Color:	Not available
Odor:	Not available
Odour threshold:	Not applicable (N/A) *

##### Volatility:

Boiling point at atmospheric pressure:	642 °F
Vapour pressure at 74 °F:	1 Pa
Vapour pressure at 122 °F:	8.8 Pa (0.01 kPa)
Evaporation rate at 74 °F:	Not applicable (N/A) *

##### Product description:

Density at 74 °F:	1806.7 kg/m <sup>3</sup>
Relative density at 74 °F:	1.807
Dynamic viscosity at 74 °F:	75.15 cP
Kinematic viscosity at 74 °F:	41.6 mm <sup>2</sup> /s
Kinematic viscosity at 104 °F:	>20.5 mm <sup>2</sup> /s
Concentration:	Not applicable (N/A) *
pH:	Not applicable (N/A) *
Vapour density at 74 °F:	Not applicable (N/A) *
Partition coefficient n-octanol/water 74 °F:	Not applicable (N/A) *
Solubility in water at 74 °F:	Not applicable (N/A) *
Solubility properties:	Not applicable (N/A) *
Decomposition temperature:	Not applicable (N/A) *
Melting point/freezing point:	Not applicable (N/A) *

##### Flammability:

Flash Point:	Non Flammable (>199.4 °F)
Flammability (solid, gas):	Not applicable (N/A) *
Autoignition temperature:	761 °F
Lower flammability limit:	Not applicable (N/A) *
Upper flammability limit:	Not applicable (N/A) *

##### Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

#### 9.2 Other information:

##### Information with regard to physical hazard classes:

Explosive properties:	Not applicable (N/A) *
Oxidising properties:	Not applicable (N/A) *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



## MS Joint Sealant Non-Sag, Gray



### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Corrosive to metals:	Not applicable (N/A) *
Heat of combustion:	Not applicable (N/A) *
Aerosols-total percentage (by mass) of flammable components:	Not applicable (N/A) *
<b>Other safety characteristics:</b>	
Surface tension at 74 °F:	Not applicable (N/A) *
Refraction index:	Not applicable (N/A) *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

#### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

##### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

- CONTINUED ON NEXT PAGE -



## MS Joint Sealant Non-Sag, Gray



### SECTION 11: TOXICOLOGICAL INFORMATION (continued)

#### D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.  
IARC: Titanium dioxide (2B); Carbon black (2B)
- Mutagenicity: Exposure to this product can cause genetic modifications. For more specific information on the possible health effects see section 2.
- Reproductive toxicity: May damage fertility or the unborn child

#### E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

#### F- Specific target organ toxicity (STOT) - single exposure:

Its ingestion, inhalation or absorption through the skin results in the risk of serious irreversible effects caused by a single exposure, not including effects which are carcinogenic, mutagenic or toxic for reproduction.

#### G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged consumption, including death, serious functional disorders or morphological changes of toxicological importance.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### Other information:

Not applicable (N/A)

#### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Trimethoxyvinylsilane CAS: 2768-02-7	7236 mg/kg	3880 mg/kg	Rat
	>20 mg/L		Rabbit
Dibutyltin oxide CAS: 818-08-6	500 mg/kg (ATEi)	>5000 mg/kg	Rat
	>5 mg/L		
Carbon black CAS: 1333-86-4	>5000 mg/kg	>5000 mg/kg	
	>5 mg/L		

#### Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	50000 mg/kg (Calculation method)	0 %
Dermal	>5000 mg/kg (Calculation method)	Non-applicable
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

### SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### 12.1 Ecotoxicity (aquatic and terrestrial, where available):

##### Acute toxicity:

- CONTINUED ON NEXT PAGE -





**MS Joint Sealant Non-Sag, Gray**



**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Concentration		Species	Genus
Trimethoxyvinylsilane CAS: 2768-02-7	LC50	191 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	167 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	957 mg/L (72 h)	N/A	Algae
Dibutyltin oxide CAS: 818-08-6	LC50	3.1 mg/L (96 h)	Danio rerio	Fish
	EC50	2 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	>1.6 mg/L (72 h)	Desmodesmus subspicatus	Algae
Carbon black CAS: 1333-86-4	LC50	1000 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	5600 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	Not applicable (N/A)		

**Chronic toxicity:**

Identification	Concentration		Species	Genus
Trimethoxyvinylsilane CAS: 2768-02-7	NOEC	Not applicable (N/A)		
	NOEC	28.1 mg/L	Daphnia magna	Crustacean

**12.2 Persistence and degradability:**

**Substance-specific information:**

Identification	Degradability		Biodegradability	
Trimethoxyvinylsilane CAS: 2768-02-7	BOD5	Not applicable (N/A)	Concentration	104 mg/L
	COD	Not applicable (N/A)	Period	28 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	51 %

**12.3 Bioaccumulative potential:**

Not available

**12.4 Mobility in soil:**

Not available

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Disposal methods:**

IT IS THE RESPONSIBILITY OF THE WASTE GENERATOR TO EVALUATE WHETHER HIS WASTES ARE HAZARDOUS BY CHARACTERISTICS OR LISTING.

**Waste management (disposal and evaluation):**

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

**Regulations related to waste management:**

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

**SECTION 14: TRANSPORT INFORMATION**

This product is not regulated for transport.

- CONTINUED ON NEXT PAGE -



## MS Joint Sealant Non-Sag, Gray



### SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations specific for the product in question:

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *Carbon black (1333-86-4)*; *Dibutyltin oxide (818-08-6)*; *Di- 'isononyl' ' phthalate (28553-12-0)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: Not applicable (N/A)
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: *Di- 'isononyl' ' phthalate (28553-12-0)*
- CANADA-Domestic Substances List (DSL): *Calcium Carbonate (471-34-1)*; *Titanium dioxide (13463-67-7)*; *Carbon black (1333-86-4)*; *Trimethoxyvinylsilane (2768-02-7)*; *Dibutyltin oxide (818-08-6)*; *Di- 'isononyl' ' phthalate (28553-12-0)*
- CANADA-Non-Domestic Substances List (NDSL): *Limestone (1317-65-3)*
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: Not applicable (N/A)
- Hazardous Air Pollutants (Clean Air Act): Not applicable (N/A)
- Massachusetts RTK - Substance List: *Limestone (1317-65-3)*; *Titanium dioxide (13463-67-7)*; *Carbon black (1333-86-4)*
- Minnesota - Hazardous substances ERTK: *Limestone (1317-65-3)*; *Titanium dioxide (13463-67-7)*; *Carbon black (1333-86-4)*; *Dibutyltin oxide (818-08-6)*
- New Jersey Worker and Community Right-to-Know Act: *Limestone (1317-65-3)*; *Titanium dioxide (13463-67-7)*; *Carbon black (1333-86-4)*
- New York RTK - Substance list: *Titanium dioxide (13463-67-7)*; *Di- 'isononyl' ' phthalate (28553-12-0)*
- NTP (National Toxicology Program): Not applicable (N/A)
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Not applicable (N/A)
- Pennsylvania Worker and Community Right-to-Know Law: *Limestone (1317-65-3)*; *Titanium dioxide (13463-67-7)*; *Carbon black (1333-86-4)*
- Rhode Island - Hazardous substances RTK: Not applicable (N/A)
- The Toxic Substances Control Act (TSCA) : *Limestone (1317-65-3)*; *Calcium Carbonate (471-34-1)*; *Titanium dioxide (13463-67-7)*; *Carbon black (1333-86-4)*; *Trimethoxyvinylsilane (2768-02-7)*; *Dibutyltin oxide (818-08-6)*; *Di- 'isononyl' ' phthalate (28553-12-0)*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): Not applicable (N/A)

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

#### Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

### SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

#### Texts of the legislative phrases mentioned in section 2:

- H351: Suspected of causing cancer.
- H317: May cause an allergic skin reaction.
- H341: Suspected of causing genetic defects.
- H360: May damage fertility or the unborn child.
- H372: Causes damage to organs through prolonged or repeated exposure.
- H370: Causes damage to organs.
- H319: Causes serious eye irritation.

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### 29 CFR 1910.1200:

- CONTINUED ON NEXT PAGE -



## MS Joint Sealant Non-Sag, Gray



### SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H302 - Harmful if swallowed.  
Acute Tox. 4: H332 - Harmful if inhaled.  
Carc. 2: H351 - Suspected of causing cancer.  
Eye Dam. 1: H318 - Causes serious eye damage.  
Flam. Liq. 3: H226 - Flammable liquid and vapour.  
Muta. 2: H341 - Suspected of causing genetic defects.  
Repr. 1B: H360 - May damage fertility or the unborn child.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
Skin Sens. 1B: H317 - May cause an allergic skin reaction.  
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.  
STOT SE 1: H370 - Causes damage to organs.

#### Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

#### Abbreviations and acronyms:

IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5-day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
CL50: Lethal Concentration 50  
EC50: Effective concentration 50  
Log-POW: Octanol-water partition coefficient  
Koc: Partition coefficient of organic carbon  
IARC: International Agency for Research on Cancer

Date of compilation: 11/7/2023

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET