



## PSW-TG LV2



### SECTION 1: IDENTIFICATION

- 1.1 GHS Product identifier:** PSW-TG LV2  
**Other means of identification:**  
Not applicable (N/A)
- 1.2 Recommended use of the chemical and restrictions on use:**  
Relevant uses: Adhesive coating. For professional users/industrial user only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:**  
The Ruscoe Company  
485 Kenmore Blvd  
44301 Akron - United States  
Phone: 330-253-8148  
Sales@Ruscoe.com; SDS@Ruscoe.com  
www.ruscoe.com
- 1.4 Emergency phone number:** Chemtrec 1-800-424-9300

### SECTION 2: HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture:**  
**29 CFR 1910.1200:**  
Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.  
Eye Irrit. 2A: Eye irritation, Category 2A, H319  
Flam. Liq. 2: Flammable liquids, Category 2, H225  
Repr. 2: Reproductive toxicity, Category 2, H361  
Skin Irrit. 2: Skin irritation, Category 2, H315  
Skin Sens. 1: Sensitisation, skin, Category 1, H317  
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

**2.2 Label elements:**

**29 CFR 1910.1200:**

Danger



**Hazard statements:**

Eye Irrit. 2A: H319 - Causes serious eye irritation.  
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.  
Repr. 2: H361 - Suspected of damaging fertility or the unborn child.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
STOT SE 3: H336 - May cause drowsiness or dizziness.

**Precautionary statements:**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.  
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313: IF exposed or concerned: Get medical advice/attention.  
P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.  
P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

**Substances that contribute to the classification**

METHYL ACETATE (CAS: 79-20-9); ACETONE (CAS: 67-64-1); ISOPROPYLIDENEDIPHENOL DIGLYCIDYL ETHER (CAS: 1675-54-3); Methyl Ethyl Ketone (CAS: 78-93-3)

- CONTINUED ON NEXT PAGE -



## SECTION 2: HAZARD(S) IDENTIFICATION (continued)

### Additional labeling:



#### WARNING

This product can expose you to chemicals including methanol, 1-chloro-2,3-epoxypropane, 1,3-butadiene, which is [are] known to the State of California to cause cancer, and 1-chloro-2,3-epoxypropane, Acrylonitrile, 1,3-butadiene, acetaldehyde, Vinyl chloride, Silicon dioxide (RCS < 1%), which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### 2.3 Hazards not otherwise classified (HNOC):

Not applicable (N/A)

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances:

Non-applicable

### 3.2 Mixtures:

**Chemical description:** Mixture composed of additives, pigments and resins in solvents

#### Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 79-20-9	<b>methyl acetate</b> Eye Irrit. 2A: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	10 - <25 %
CAS: 67-64-1	<b>acetone</b> Eye Irrit. 2A: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	10 - <25 %
CAS: 1675-54-3	<b>Bis-[4-(2,3-epoxypropoxy)phenyl]propane</b> Eye Irrit. 2A: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	2.5 - <10 %
CAS: 78-93-3	<b>Methyl Ethyl Ketone</b> Eye Irrit. 2A: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	1 - <2.5 %
CAS: 2386-87-0	<b>7-oxabicyclo[4.1.0]hept-3-ylmethyl 7-oxabicyclo[4.1.0]heptane-3-carboxylate</b> Skin Sens. 1B: H317 - Warning	<1 %
CAS: 2440-22-4	<b>2-(2H-benzotriazol-2-yl)-p-cresol</b> Skin Sens. 1B: H317 - Warning	<1 %
CAS: 68610-51-5	<b>Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene</b> Repr. 2: H361 - Warning	<1 %
CAS: 106990-43-6	<b>N,N,N,N-tetrakis(4,6-bis(butyl- (N-methyl-2,2,6,6-tetramethyl piperidin-4-yl)amino)triazin-2-yl)-4,7-diazadecane-1,10-diamine</b> Skin Sens. 1: H317 - Warning	<1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

## SECTION 4: FIRST-AID MEASURES

### 4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

#### By skin contact:

- CONTINUED ON NEXT PAGE -



#### SECTION 4: FIRST-AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms/effects, acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of immediate medical attention and special treatment needed, if necessary:**

Not available

#### SECTION 5: FIRE-FIGHTING MEASURES

**5.1 Suitable (and unsuitable) extinguishing media:**

**Suitable extinguishing media:**

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

**Unsuitable extinguishing media:**

Water jet

**5.2 Specific hazards arising from the chemical:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Special protective equipment and precautions for fire-fighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

**Additional provisions:**

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

**6.1 Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

**6.3 Methods and materials for containment and cleaning up:**

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

- CONTINUED ON NEXT PAGE -



**PSW-TG LV2**



**SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Because the product is a flammable liquid, storage should meet the requirement of 29 CFR 1910.106, Flammable and Combustible Liquids Code. Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems and with the minimum requirements for protecting the security and health of workers. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in fixed places that comply with the necessary security conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to containers of small amounts. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Specific storage requirements

Minimum Temp.: 41 °F  
Maximum Temp.: 90 °F

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
	8-hour TWA PEL	200 ppm	610 mg/m <sup>3</sup>
methyl acetate CAS: 79-20-9	Ceiling Values - TWA PEL		
methanol <sup>(1)</sup> CAS: 67-56-1	8-hour TWA PEL	200 ppm	260 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
acetone CAS: 67-64-1	8-hour TWA PEL	1000 ppm	2400 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
	8-hour TWA PEL	100 ppm	300 mg/m <sup>3</sup>
2-methylpropan-2-ol CAS: 75-65-0	Ceiling Values - TWA PEL		
tert-butyl acetate CAS: 540-88-5	8-hour TWA PEL	200 ppm	950 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
Cyclohexanone <sup>(1)</sup> CAS: 108-94-1	8-hour TWA PEL	50 ppm	200 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
1-chloro-2,3-epoxypropane <sup>(1)</sup> CAS: 106-89-8	8-hour TWA PEL	5 ppm	19 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
Acrylonitrile <sup>(2)</sup> CAS: 107-13-1	8-hour TWA PEL	1 ppm	
	Ceiling Values - TWA PEL	10 ppm	
1,3-butadiene CAS: 106-99-0	8-hour TWA PEL	1 ppm	
	Ceiling Values - TWA PEL		
acetaldehyde CAS: 75-07-0	8-hour TWA PEL	200 ppm	360 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
Vinyl chloride CAS: 75-01-4	8-hour TWA PEL	1 ppm	
	Ceiling Values - TWA PEL	5 ppm	
Calcium sulfate CAS: 7778-18-9	8-hour TWA PEL		5 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
Methyl Ethyl Ketone CAS: 78-93-3	8-hour TWA PEL	200 ppm	590 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		
Titanium dioxide CAS: 13463-67-7	8-hour TWA PEL		15 mg/m <sup>3</sup>
	Ceiling Values - TWA PEL		

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		
	TLV-TWA	200 ppm	
methyl acetate CAS: 79-20-9	TLV-STEL	250 ppm	
methanol <sup>(1)</sup> CAS: 67-56-1	TLV-TWA	200 ppm	
	TLV-STEL	250 ppm	
acetone CAS: 67-64-1	TLV-TWA	250 ppm	
	TLV-STEL	500 ppm	
2-methylpropan-2-ol CAS: 75-65-0	TLV-TWA	100 ppm	
	TLV-STEL		
tert-butyl acetate CAS: 540-88-5	TLV-TWA	200 ppm	
	TLV-STEL		
Cyclohexanone <sup>(1)</sup> CAS: 108-94-1	TLV-TWA	20 ppm	
	TLV-STEL	50 ppm	
1-chloro-2,3-epoxypropane <sup>(1)</sup> CAS: 106-89-8	TLV-TWA	0.1 ppm	
	TLV-STEL		
Talc CAS: 14807-96-6	TLV-TWA		2 mg/m <sup>3</sup>
	TLV-STEL		
Quartz (RCS > 10%) CAS: 14808-60-7	TLV-TWA		0.025 mg/m <sup>3</sup>
	TLV-STEL		
Acrylonitrile <sup>(2)</sup> CAS: 107-13-1	TLV-TWA	2 ppm	
	TLV-STEL		
1,3-butadiene CAS: 106-99-0	TLV-TWA	2 ppm	
	TLV-STEL		
vinyl acetate CAS: 108-05-4	TLV-TWA	10 ppm	
	TLV-STEL	15 ppm	
Vinyl chloride CAS: 75-01-4	TLV-TWA	1 ppm	
	TLV-STEL		

- CONTINUED ON NEXT PAGE -



**PSW-TG LV2**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		
	TLV-TWA	TLV-STEL	TLV-C
Calcium sulfate CAS: 7778-18-9			10 mg/m <sup>3</sup>
Quartz (1 % < RCS < 10%) CAS: 14808-60-7			0.025 mg/m <sup>3</sup>
Methyl Ethyl Ketone CAS: 78-93-3	50 ppm	100 ppm	
Titanium dioxide CAS: 13463-67-7			2.5 mg/m <sup>3</sup>
Aluminium hydroxide CAS: 21645-51-2			1 mg/m <sup>3</sup>
propanal CAS: 123-38-6	20 ppm		

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occupational exposure limits		
	PEL	STEL	TLV-C
methyl acetate CAS: 79-20-9	200 ppm	760 mg/m <sup>3</sup>	610 mg/m <sup>3</sup>
methanol <sup>(1)</sup> CAS: 67-56-1	200 ppm	325 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>
acetone CAS: 67-64-1	500 ppm	1780 mg/m <sup>3</sup>	1200 mg/m <sup>3</sup>
2-methylpropan-2-ol CAS: 75-65-0	100 ppm	450 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>
tert-butyl acetate CAS: 540-88-5	200 ppm	950 mg/m <sup>3</sup>	
Cyclohexanone <sup>(1)</sup> CAS: 108-94-1	25 ppm	100 mg/m <sup>3</sup>	
Talc CAS: 14807-96-6			2 mg/m <sup>3</sup>
Quartz (RCS > 10%) CAS: 14808-60-7			0.05 mg/m <sup>3</sup>
Acrylonitrile <sup>(2)</sup> CAS: 107-13-1	2 ppm	4.5 mg/m <sup>3</sup>	
1,3-butadiene CAS: 106-99-0	1 ppm	11 mg/m <sup>3</sup>	2.2 mg/m <sup>3</sup>
vinyl acetate CAS: 108-05-4	10 ppm	45 mg/m <sup>3</sup>	30 mg/m <sup>3</sup>
acetaldehyde CAS: 75-07-0	25 ppm	45 mg/m <sup>3</sup>	
Vinyl chloride CAS: 75-01-4	1 ppm		
Quartz (1 % < RCS < 10%) CAS: 14808-60-7			0.05 mg/m <sup>3</sup>

<sup>(1)</sup> Skin

<sup>(2)</sup> Skin. Dermal sensitisation

**Biological limit values:**

Biological Exposure Indices (BEIs®) - ACGIH

Identification	BEIs®	Determinant	Sampling Time
methanol CAS: 67-56-1	15 mg/L	Methanol in urine	End of shift
acetone CAS: 67-64-1	25 mg/L	Acetone in urine	End of shift
Cyclohexanone CAS: 108-94-1	8 mg/L	Cyclohexanol in urine	End of shift
1,3-butadiene CAS: 106-99-0	2.5 mg/L	1,2 Dihydroxy-4-(N-acetylcysteinyl)-butane in urine	End of shift
Methyl Ethyl Ketone CAS: 78-93-3	2 mg/L	Methyl ethyl ketone in urine	End of shift

- CONTINUED ON NEXT PAGE -




**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

**8.2 Appropriate engineering controls:**


A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection


Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR)

C.- Specific protection for the hands



Pictogram	PPE	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

E.- Bodily protection

Pictogram	PPE	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer's use limitations and OSHA standard 1910.136 (29CFR)

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

- CONTINUED ON NEXT PAGE -



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

#### Appearance:

Physical state at 68 °F:	Liquid
Appearance:	Not available
Color:	Not available
Odor:	Not available
Odour threshold:	Not available *

#### Volatility:

Boiling point at atmospheric pressure:	145 °F
Vapour pressure at 74 °F:	23934 Pa
Vapour pressure at 122 °F:	70104.92 Pa (70.1 kPa)
Evaporation rate at 74 °F:	Not available *

#### Product description:

Density at 74 °F:	1121 kg/m <sup>3</sup>
Relative density at 74 °F:	1.121
Dynamic viscosity at 74 °F:	Not available *
Kinematic viscosity at 74 °F:	Not available *
Kinematic viscosity at 104 °F:	Not available *
Concentration:	Not available *
pH:	Not available *
Vapour density at 74 °F:	Not available *
Partition coefficient n-octanol/water 74 °F:	Not available *
Solubility in water at 74 °F:	Not available *
Solubility properties:	Not available *
Decomposition temperature:	Not available *
Melting point/freezing point:	Not available *

#### Flammability:

Flash Point:	13 °F
Flammability (solid, gas):	Not available *
Autoignition temperature:	365 °F
Lower flammability limit:	Not available
Upper flammability limit:	Not available

#### Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

### 9.2 Other information:

#### Information with regard to physical hazard classes:

Explosive properties:	Not available *
Oxidising properties:	Not available *
Corrosive to metals:	Not available *
Heat of combustion:	Not available *
Aerosols-total percentage (by mass) of flammable components:	Not available *

#### Other safety characteristics:

\*Not available due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -





## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Surface tension at 74 °F: Not available \*  
Refraction index: Not available \*

\*Not available due to the nature of the product, not providing information property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

#### A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

#### B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

#### D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- CONTINUED ON NEXT PAGE -



**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Cyclohexanone (3); Bis-[4-(2,3-epoxypropoxy)phenyl]propane (3); 1-chloro-2,3-epoxypropane (2A); Talc (3); Quartz (RCS > 10%) (1); Acrylonitrile (2B); 1,3-butadiene (1); vinyl acetate (2B); acetaldehyde (2B); Vinyl chloride (1); Quartz (1 % < RCS < 10%) (1); Titanium dioxide (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging fertility or the unborn child

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Not applicable (N/A)

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
methyl acetate CAS: 79-20-9	6482 mg/kg	18684 mg/kg	Rat
		75 mg/L (4 h)	Guinean pig
			Rabbit
acetone CAS: 67-64-1	5800 mg/kg	7426 mg/kg	Rat
		76 mg/L (4 h)	Rabbit
			Rat
Bis-[4-(2,3-epoxypropoxy)phenyl]propane CAS: 1675-54-3	>5000 mg/kg	20000 mg/kg	Rabbit
		>5 mg/L	
Methyl Ethyl Ketone CAS: 78-93-3	4000 mg/kg	6400 mg/kg	Rat
		23.5 mg/L (4 h)	Rabbit
			Rat
7-oxabicyclo[4.1.0]hept-3-ylmethyl 7-oxabicyclo[4.1.0]heptane-3-carboxylate CAS: 2386-87-0	4490 mg/kg	>5000 mg/kg	Rat
		>20 mg/L	
2-(2H-benzotriazol-2-yl)-p-cresol CAS: 2440-22-4	10000 mg/kg	>5000 mg/kg	Rat
		>5 mg/L	
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene CAS: 68610-51-5	>5000 mg/kg	>5000 mg/kg	Rat
		>5 mg/L	
N,N,N,N-tetrakis(4,6-bis(butyl- (N-methyl-2,2,6,6-tetramethyl piperidin-4-yl)amino)triazin-2-yl)-4,7-diazadecane-1,10- diamine CAS: 106990-43-6	>5000 mg/kg	>5000 mg/kg	
		>5 mg/L	

**Acute Toxicity Estimate (ATE mix):**

- CONTINUED ON NEXT PAGE -



**PSW-TG LV2**



**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

ATE mix		Ingredient(s) of unknown toxicity
Oral	43402.9 mg/kg (Calculation method)	Non-applicable
Dermal	>5000 mg/kg (Calculation method)	Non-applicable
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**12.1 Ecotoxicity (aquatic and terrestrial, where available):**

**Acute toxicity:**

Identification	Concentration		Species	Genus
	LC50	EC50		
methyl acetate CAS: 79-20-9	LC50	320 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1026.7 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	120 mg/L (72 h)	Scenedesmus subspicatus	Algae
acetone CAS: 67-64-1	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean
	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
Methyl Ethyl Ketone CAS: 78-93-3	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae

**Chronic toxicity:**

Identification	Concentration		Species	Genus
	NOEC	Concentration		
acetone CAS: 67-64-1	NOEC	Not applicable (N/A)		
	NOEC	2212 mg/L	Daphnia magna	Crustacean
2-(2H-benzotriazol-2-yl)-p-cresol CAS: 2440-22-4	NOEC	Not applicable (N/A)		
	NOEC	0.013 mg/L	Daphnia magna	Crustacean

**12.2 Persistence and degradability:**

**Substance-specific information:**

Identification	Degradability		Biodegradability	
	Parameter	Value	Parameter	Value
methyl acetate CAS: 79-20-9	BOD5	Not applicable (N/A)	Concentration	100 mg/L
	COD	Not applicable (N/A)	Period	14 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	92 %
acetone CAS: 67-64-1	BOD5	Not applicable (N/A)	Concentration	100 mg/L
	COD	Not applicable (N/A)	Period	28 days
	BOD5/COD	Not applicable (N/A)	% Biodegradable	96 %
Methyl Ethyl Ketone CAS: 78-93-3	BOD5	2.03 g O2/g	Concentration	Not applicable (N/A)
	COD	2.31 g O2/g	Period	20 days
	BOD5/COD	0.88	% Biodegradable	89 %

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

Identification	Bioaccumulation potential	
	Parameter	Value
methyl acetate CAS: 79-20-9	BCF	0.8
	Pow Log	0.18
	Potential	Low

- CONTINUED ON NEXT PAGE -



**PSW-TG LV2**



**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Bioaccumulation potential	
	BCF	Pow Log
acetone CAS: 67-64-1	1	-0.24
Methyl Ethyl Ketone CAS: 78-93-3	3	0.29
2-(2H-benzotriazol-2-yl)-p-cresol CAS: 2440-22-4	123	4.2
	Potential	Low
	Potential	Low
	Potential	High

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
	Koc	Conclusion	Henry	Conclusion
methyl acetate CAS: 79-20-9	Not applicable (N/A)	Not applicable (N/A)	Not applicable (N/A)	Not applicable (N/A)
			Dry soil	Not applicable (N/A)
	Surface tension	2.454E-2 N/m (77 °F)	Moist soil	Not applicable (N/A)
acetone CAS: 67-64-1	1	Very High	2.93 Pa·m <sup>3</sup> /mol	Yes
			Dry soil	Yes
	Surface tension	2.304E-2 N/m (77 °F)	Moist soil	Yes
Methyl Ethyl Ketone CAS: 78-93-3	30	Very High	5.77 Pa·m <sup>3</sup> /mol	Yes
			Dry soil	Yes
	Surface tension	2.396E-2 N/m (77 °F)	Moist soil	Yes

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Disposal methods:**

The next characteristic per RCRA could apply to the unused product if it becomes a waste material: Ignitability. The next EPA hazardous waste number could apply: D001.  
IT IS THE RESPONSIBILITY OF THE WASTE GENERATOR TO EVALUATE WHETHER HIS WASTES ARE HAZARDOUS BY CHARACTERISTICS OR LISTING.

**Waste management (disposal and evaluation):**

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

**Regulations related to waste management:**

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to 49 CFR on the Transport of Dangerous Goods:

- CONTINUED ON NEXT PAGE -



SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN1133  
**14.2 UN proper shipping name:** ADHESIVES  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group, if applicable:** II  
**14.5 Marine pollutant:** No  
**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
 Physico-Chemical properties: see section 9  
 Limited quantities: 5 L  
**14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable (N/A)

**Transport of dangerous goods by sea:**

With regard to IMDG 41-22:



- 14.1 UN number:** UN1133  
**14.2 UN proper shipping name:** ADHESIVES  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group, if applicable:** II  
**14.5 Marine pollutant:** No  
**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
 Special regulations: Not applicable (N/A)  
 EmS Codes: F-E, S-D  
 Physico-Chemical properties: see section 9  
 Limited quantities: 5 L  
 Segregation group: Not applicable (N/A)  
**14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable (N/A)

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2024:



- 14.1 UN number:** UN1133  
**14.2 UN proper shipping name:** ADHESIVES  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group, if applicable:** II  
**14.5 Marine pollutant:** No  
**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
 Physico-Chemical properties: see section 9  
**14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable (N/A)

SECTION 15: REGULATORY INFORMATION

- 15.1 Safety, health and environmental regulations specific for the product in question:**

- CONTINUED ON NEXT PAGE -



SECTION 15: REGULATORY INFORMATION (continued)

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *methyl acetate (79-20-9)*; *methanol (67-56-1)*; *acetone (67-64-1)*; *2-methylpropan-2-ol (75-65-0)*; *tert-butyl acetate (540-88-5)*; *Cyclohexanone (108-94-1)*; *1-chloro-2,3-epoxypropane (106-89-8)*; *Talc (14807-96-6)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*; *vinyl acetate (108-05-4)*; *acetaldehyde (75-07-0)*; *Vinyl chloride (75-01-4)*; *Methyl Ethyl Ketone (78-93-3)*; *Silicon dioxide (RCS < 1%) (7631-86-9)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: *methanol (67-56-1)*; *1-chloro-2,3-epoxypropane (106-89-8)*; *1,3-butadiene (106-99-0)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: *1-chloro-2,3-epoxypropane (106-89-8)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*; *acetaldehyde (75-07-0)*; *Vinyl chloride (75-01-4)*; *Silicon dioxide (RCS < 1%) (7631-86-9)*
- CANADA-Domestic Substances List (DSL): *methyl acetate (79-20-9)*; *methanol (67-56-1)*; *acetone (67-64-1)*; *2-methylpropan-2-ol (75-65-0)*; *tert-butyl acetate (540-88-5)*; *Cyclohexanone (108-94-1)*; *Bis-[4-(2,3-epoxypropoxy)phenyl]propane (1675-54-3)*; *1-chloro-2,3-epoxypropane (106-89-8)*; *NBR (9003-18-3)*; *Talc (14807-96-6)*; *Quartz (RCS > 10%) (14808-60-7)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*; *N,N,N,N-tetrakis(4,6-bis(butyl-(N-methyl-2,2,6,6-tetramethyl piperidin-4-yl)amino)triazin-2-yl)-4,7-diazadecane-1,10-diamine (106990-43-6)*; *7-oxabicyclo[4.1.0]hept-3-ylmethyl 7-oxabicyclo[4.1.0]heptane-3-carboxylate (2386-87-0)*; *vinyl acetate (108-05-4)*; *acetaldehyde (75-07-0)*; *Vinyl chloride (75-01-4)*; *Calcium sulfate (7778-18-9)*; *Quartz (1 % < RCS < 10%) (14808-60-7)*; *Methyl Ethyl Ketone (78-93-3)*; *Sulfonic acids, petroleum, calcium salts (TBN < 300) (61789-86-4)*; *Titanium dioxide (13463-67-7)*; *Aluminium hydroxide (21645-51-2)*; *Silicon dioxide (RCS < 1%) (7631-86-9)*; *Propylidynetrimethanol (77-99-6)*; *propanal (123-38-6)*; *Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene (68610-51-5)*; *2-(2H-benzotriazol-2-yl)-p-cresol (2440-22-4)*
- CANADA-Non-Domestic Substances List (NDSL): Not applicable (N/A)
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: *methanol (67-56-1) - U154*; *acetone (67-64-1) - U002*; *tert-butyl acetate (540-88-5) - 5000 lb*; *Cyclohexanone (108-94-1) - U057*; *1-chloro-2,3-epoxypropane (106-89-8) - U041*; *Acrylonitrile (107-13-1) - U009*; *1,3-butadiene (106-99-0) - 10 lb*; *vinyl acetate (108-05-4) - 5000 lb*; *acetaldehyde (75-07-0) - U001*; *Vinyl chloride (75-01-4) - U043*; *Methyl Ethyl Ketone (78-93-3) - U159*; *propanal (123-38-6) - 1000 lb*
- Hazardous Air Pollutants (Clean Air Act): *methanol (67-56-1)*; *1-chloro-2,3-epoxypropane (106-89-8)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*; *vinyl acetate (108-05-4)*; *acetaldehyde (75-07-0)*; *Vinyl chloride (75-01-4)*; *propanal (123-38-6)*
- Massachusetts RTK - Substance List: *methyl acetate (79-20-9)*; *methanol (67-56-1)*; *acetone (67-64-1)*; *2-methylpropan-2-ol (75-65-0)*; *tert-butyl acetate (540-88-5)*; *Cyclohexanone (108-94-1)*; *1-chloro-2,3-epoxypropane (106-89-8)*; *Talc (14807-96-6)*; *Quartz (RCS > 10%) (14808-60-7)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*; *vinyl acetate (108-05-4)*; *acetaldehyde (75-07-0)*; *Vinyl chloride (75-01-4)*; *Calcium sulfate (7778-18-9)*; *Quartz (1 % < RCS < 10%) (14808-60-7)*; *Methyl Ethyl Ketone (78-93-3)*; *Titanium dioxide (13463-67-7)*; *Silicon dioxide (RCS < 1%) (7631-86-9)*; *propanal (123-38-6)*
- Minnesota - Hazardous substances ERTK: *methyl acetate (79-20-9)*; *methanol (67-56-1)*; *acetone (67-64-1)*; *2-methylpropan-2-ol (75-65-0)*; *tert-butyl acetate (540-88-5)*; *Cyclohexanone (108-94-1)*; *1-chloro-2,3-epoxypropane (106-89-8)*; *Talc (14807-96-6)*; *Quartz (RCS > 10%) (14808-60-7)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*; *vinyl acetate (108-05-4)*; *acetaldehyde (75-07-0)*; *Vinyl chloride (75-01-4)*; *Calcium sulfate (7778-18-9)*; *Quartz (1 % < RCS < 10%) (14808-60-7)*; *Methyl Ethyl Ketone (78-93-3)*; *Titanium dioxide (13463-67-7)*; *Silicon dioxide (RCS < 1%) (7631-86-9)*
- New Jersey Worker and Community Right-to-Know Act: *methyl acetate (79-20-9)*; *methanol (67-56-1)*; *acetone (67-64-1)*; *2-methylpropan-2-ol (75-65-0)*; *tert-butyl acetate (540-88-5)*; *Cyclohexanone (108-94-1)*; *1-chloro-2,3-epoxypropane (106-89-8)*; *Talc (14807-96-6)*; *Quartz (RCS > 10%) (14808-60-7)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*; *vinyl acetate (108-05-4)*; *acetaldehyde (75-07-0)*; *Vinyl chloride (75-01-4)*; *Calcium sulfate (7778-18-9)*; *Quartz (1 % < RCS < 10%) (14808-60-7)*; *Methyl Ethyl Ketone (78-93-3)*; *Titanium dioxide (13463-67-7)*; *propanal (123-38-6)*
- New York RTK - Substance list: *methyl acetate (79-20-9)*; *methanol (67-56-1)*; *acetone (67-64-1)*; *2-methylpropan-2-ol (75-65-0)*; *tert-butyl acetate (540-88-5)*; *Cyclohexanone (108-94-1)*; *Bis-[4-(2,3-epoxypropoxy)phenyl]propane (1675-54-3)*; *1-chloro-2,3-epoxypropane (106-89-8)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*; *vinyl acetate (108-05-4)*; *acetaldehyde (75-07-0)*; *Vinyl chloride (75-01-4)*; *Methyl Ethyl Ketone (78-93-3)*; *Titanium dioxide (13463-67-7)*; *propanal (123-38-6)*
- NTP (National Toxicology Program): *1-chloro-2,3-epoxypropane (106-89-8)*; *Quartz (RCS > 10%) (14808-60-7)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*; *acetaldehyde (75-07-0)*; *Vinyl chloride (75-01-4)*; *Quartz (1 % < RCS < 10%) (14808-60-7)*; *Silicon dioxide (RCS < 1%) (7631-86-9)*
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): *Quartz (RCS > 10%) (14808-60-7)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*; *Vinyl chloride (75-01-4)*; *Quartz (1 % < RCS < 10%) (14808-60-7)*; *Silicon dioxide (RCS < 1%) (7631-86-9)*
- Pennsylvania Worker and Community Right-to-Know Law: *methyl acetate (79-20-9)*; *methanol (67-56-1)*; *acetone (67-64-1)*; *2-methylpropan-2-ol (75-65-0)*; *tert-butyl acetate (540-88-5)*; *Cyclohexanone (108-94-1)*; *1-chloro-2,3-epoxypropane (106-89-8)*; *Talc (14807-96-6)*; *Quartz (RCS > 10%) (14808-60-7)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*; *vinyl acetate (108-05-4)*; *acetaldehyde (75-07-0)*; *Vinyl chloride (75-01-4)*; *Calcium sulfate (7778-18-9)*; *Quartz (1 % < RCS < 10%) (14808-60-7)*; *Methyl Ethyl Ketone (78-93-3)*; *Titanium dioxide (13463-67-7)*; *Silicon dioxide (RCS < 1%) (7631-86-9)*; *propanal (123-38-6)*
- Rhode Island - Hazardous substances RTK: *methanol (67-56-1)*; *acetone (67-64-1)*; *tert-butyl acetate (540-88-5)*; *Cyclohexanone (108-94-1)*; *1-chloro-2,3-epoxypropane (106-89-8)*; *Acrylonitrile (107-13-1)*; *1,3-butadiene (106-99-0)*; *vinyl*

- CONTINUED ON NEXT PAGE -



## SECTION 15: REGULATORY INFORMATION (continued)

*acetate (108-05-4); acetaldehyde (75-07-0); Vinyl chloride (75-01-4); Methyl Ethyl Ketone (78-93-3); propanal (123-38-6)*  
- The Toxic Substances Control Act (TSCA) (USA, Puerto Rico): *methyl acetate (79-20-9); methanol (67-56-1); acetone (67-64-1); 2-methylpropan-2-ol (75-65-0); tert-butyl acetate (540-88-5); Cyclohexanone (108-94-1); Bis-[4-(2,3-epoxypropoxy)phenyl]propane (1675-54-3); 1-chloro-2,3-epoxypropane (106-89-8); NBR (9003-18-3); Talc (14807-96-6); Quartz (RCS > 10%) (14808-60-7); Acrylonitrile (107-13-1); 1,3-butadiene (106-99-0); N,N,N-tetrakis(4,6-bis(butyl-(N-methyl-2,2,6,6-tetramethyl piperidin-4-yl)amino)triazin-2-yl)-4,7-diazadecane-1,10-diamine (106990-43-6); 7-oxabicyclo[4.1.0]hept-3-ylmethyl 7-oxabicyclo[4.1.0]heptane-3-carboxylate (2386-87-0); vinyl acetate (108-05-4); acetaldehyde (75-07-0); Vinyl chloride (75-01-4); Calcium sulfate (7778-18-9); Quartz (1% < RCS < 10%) (14808-60-7); Methyl Ethyl Ketone (78-93-3); Sulfonic acids, petroleum, calcium salts (TBN < 300) (61789-86-4); Titanium dioxide (13463-67-7); Aluminium hydroxide (21645-51-2); Silicon dioxide (RCS < 1%) (7631-86-9); Propylidynetrimethanol (77-99-6); propanal (123-38-6); Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene (68610-51-5); 2-(2H-benzotriazol-2-yl)-p-cresol (2440-22-4)*  
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): *methanol (67-56-1); 2-methylpropan-2-ol (75-65-0); 1-chloro-2,3-epoxypropane (106-89-8); Acrylonitrile (107-13-1); 1,3-butadiene (106-99-0); vinyl acetate (108-05-4); acetaldehyde (75-07-0); Vinyl chloride (75-01-4); propanal (123-38-6)*

### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

### Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

## SECTION 16: OTHER INFORMATION

### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

### Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H361: Suspected of damaging fertility or the unborn child.  
H225: Highly flammable liquid and vapour.

### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### 29 CFR 1910.1200:

Eye Irrit. 2A: H319 - Causes serious eye irritation.  
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.  
Repr. 2: H361 - Suspected of damaging fertility or the unborn child.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
Skin Sens. 1B: H317 - May cause an allergic skin reaction.  
STOT SE 3: H336 - May cause drowsiness or dizziness.

### Advice related to training:

According to 29 CFR 1910.1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

### Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

### Abbreviations and acronyms:

- CONTINUED ON NEXT PAGE -



**SECTION 16: OTHER INFORMATION (continued)**

IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5-day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
CL50: Lethal Concentration 50  
EC50: Effective concentration 50  
Log-POW: Octanol-water partition coefficient  
Koc: Partition coefficient of organic carbon  
IARC: International Agency for Research on Cancer

Date of compilation: 8/1/2023  
Revised: 4/22/2024

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET