 <b>BOSTIK</b>	Page: 1
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier**

Trade name : Pliobond™ 20  
ADHESIVE  
™ Trademark, Bostik or its subsidiaries, registered in various countries

**Relevant identified uses of the substance or mixture and uses advised against**

Recommended use : ADHESIVE


<b>Details of the supplier of the safety data sheet</b> Bostik, Inc. 11320 W Watertown Plank Road Wauwatosa, WI 53226 United States of America (USA) +1(800)843-0844; +1(414)774-2250  EHSproductsafety.US@bostik.com	<b>Emergency telephone number</b> Chemtrec 1-800-424-9300, outside US 1-703-527-3887  <b>Regulatory information</b> Rocky Mountain Poison center: 1-866-767-5089
--	--

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification**

Flammable liquids : Category 2  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Germ cell mutagenicity : Category 2  
Specific target organ toxicity : Category 3 (Central nervous system)  
- single exposure  
Specific target organ toxicity : Category 2 (Skin, Nervous system, Liver, Kidney)  
- repeated exposure

**GHS label elements**

	Page: 2
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

Hazard pictograms :   

Signal Word : Danger

Hazard Statements : Highly flammable liquid and vapor.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 May cause drowsiness or dizziness.  
 Suspected of causing genetic defects.  
 May cause damage to organs (Skin, Nervous system, Liver, Kidney) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**  
 Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
 Keep container tightly closed.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.  
 Wash skin thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF exposed or concerned: Get medical advice/ attention.  
 If skin irritation occurs: Get medical advice/ attention.  
 If eye irritation persists: Get medical advice/ attention.  
 Take off contaminated clothing and wash before reuse.  
 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
**Storage:**



# BOSTIK

## SAFETY DATA SHEET

Revision Date: 05/16/2022

Print Date: 12/6/2023

SDS Number: R0171288

Version: 3.1

Pliobond™ 20 ADHESIVE  
 ™ Trademark, Bostik or its subsidiaries, registered in various countries  
 162497

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**


None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

**Hazardous components**


Chemical name	CAS-No.	Classification	Concentration (%)
METHYL ETHYL KETONE	78-93-3	Flam. Liq. 2; H225  Eye Irrit. 2A; H319  STOT SE 3; H336	76.792
CALCIUM CARBONATE	471-34-1	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	2.7452
PHENOL	108-95-2	Comb Dust Acute Tox. 3; H301  Acute Tox. 3; H331  Acute Tox. 3; H311  Skin Corr. 1; H314  Eye Dam. 1; H318  Muta. 2; H341  STOT RE 2; H373	1.088

 <b>BOSTIK</b>	Page: 4
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

--	--	--

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Move to fresh air.  
If unconscious, place in recovery position and seek medical advice.  
Consult a physician after significant exposure.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.
- If swallowed : Obtain medical attention.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Do not induce vomiting. Phenol concentrations greater than 1.5% produce irritation and greater than 5% are corrosive; vomiting can cause further damage to the mouth and throat.  
Do not dilute the swallowed material, since this may enhance its absorption. Seek immediate medical attention. If possible, do not leave the individual unattended. Vomiting and diarrhea may occur spontaneously.
- Most important symptoms and effects, both acute and delayed : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)  
Cough  
Headache  
low body temperature  
irregular heartbeat

 <b>BOSTIK</b>	Page: 5
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

cyanosis (causes blue coloring of the skin and nails from lack of oxygen)  
lung edema (fluid buildup in the lung tissue)  
Convulsions  
respiratory failure  
Difficulty in breathing  
Ingestion of large amounts or other significant exposure to this material (or a component) may cause alkalosis.  
Excessive calcium intake may cause gastrointestinal symptoms, hypertension, hypercalcemia, kidney stones, and may inhibit absorption of iron, zinc, and possibly other trace elements.  
Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.  
Pulmonary edema may be delayed.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of causing genetic defects.  
May cause damage to organs through prolonged or repeated exposure.


Notes to physician

: Phenol adsorbs to activated charcoal, and it maybe preferable to ipecac-induced emesis because seizures or coma may onset rapidly and because of the corrosive effects of phenol. A usual activated charcoal dose in adults is 30-100 g and in children is 15-30 g. Activated charcoal should be administered with, or followed by, a cathartic. If endoscopy is planned, charcoal may obscure visualization of affected areas. Gastric lavage may be indicated if it is performed soon after ingestion or in patients who are comatose or at risk of seizures. Monitor for seizures, metabolic acidosis and ventricular dysrhythmias.

---

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Alcohol-resistant foam  
Carbon dioxide (CO2)

 <b>BOSTIK</b>	Page: 6
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

Dry chemical

Unsuitable extinguishing media : High volume water jet

Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Nitrogen oxides (NO<sub>x</sub>)  
Hydrogen cyanide (hydrocyanic acid)  
Organic acids

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.


## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Other information : Comply with all applicable federal, state, and local regulations.  
Suppress (knock down) gases/vapours/mists with a water

 <b>BOSTIK</b>	Page: 7
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

spray jet.

---

## SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
No sparking tools should be used.  
Keep away from open flames, hot surfaces and sources of ignition.  
Use only explosion-proof equipment.
- Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
- Advice on safe handling : Open drum carefully as content may be under pressure.  
Avoid formation of aerosol.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Container hazardous when empty.  
Take precautionary measures against static discharges.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
No smoking.
- Further information on storage stability : No decomposition if stored and applied as directed.



# BOSTIK

**SAFETY DATA SHEET**

Revision Date: 05/16/2022

Print Date: 12/6/2023

SDS Number: R0171288


Version: 3.1

Pliobond™ 20 ADHESIVE  
 ™ Trademark, Bostik or its subsidiaries, registered in various countries  
 162497

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
METHYL ETHYL KETONE	78-93-3	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m3	NIOSH REL
		ST	300 ppm 885 mg/m3	NIOSH REL
		TWA	200 ppm 590 mg/m3	OSHA Z-1
		TWA	200 ppm 590 mg/m3	OSHA P0
		STEL	300 ppm 885 mg/m3	OSHA P0
		PEL	200 ppm 590 mg/m3	CAL PEL
		STEL	300 ppm 885 mg/m3	CAL PEL
		CALCIUM CARBONATE	471-34-1	PEL
PEL	5 mg/m3 respirable dust fraction			CAL PEL
TWA	5 mg/m3 Respirable (Calcium carbonate)			NIOSH REL
TWA	10 mg/m3 total (Calcium carbonate)			NIOSH REL
PHENOL	108-95-2	TWA	5 ppm	ACGIH
		TWA	5 ppm 19 mg/m3	NIOSH REL
		C	15.6 ppm 60 mg/m3	NIOSH REL
		TWA	5 ppm 19 mg/m3	OSHA Z-1
		TWA	5 ppm 19 mg/m3	OSHA P0
		PEL	5 ppm	CAL PEL



		Page: 9
<b>SAFETY DATA SHEET</b>		Revision Date: 05/16/2022
		Print Date: 12/6/2023
		SDS Number: R0171288
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497		Version: 3.1

					19 mg/m3		
<b>Biological occupational exposure limits</b>							
Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis	
METHYL ETHYL KETONE	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ZUS_A CGIHB	
PHENOL	108-95-2	Phenol	Urine	End of shift (As soon as possible after exposure ceases)	250 mg/g Creatinine	ZUS_A CGIHB	

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

**Respiratory protection** : In the case of vapour formation use a respirator with an approved filter within the capabilities of the respirator/filter combination.  
Where concentrations are above recommended limits or are unknown, or a cartridge type respirator is not adequate, wear a positive-pressure supplied-air respirator.


**Hand protection**

**Material** : butyl-rubber  
**Break through time** : 480 min  
**Glove thickness** : > 0.5 mm

**Remarks** : The exact break through time can be obtained from the protective glove producer and this has to be observed. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

**Eye protection** : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

**Skin and body protection** : Wear resistant gloves (consult your safety equipment supplier).

 <b>BOSTIK</b>	Page: 10
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

Wear as appropriate:  
Impervious clothing  
Safety shoes  
Flame-resistant clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Discard gloves that show tears, pinholes, or signs of wear.

Hygiene measures : Wash hands before breaks and at the end of workday.  
When using do not eat or drink.  
When using do not smoke.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Physical state : liquid

Colour : tan

Odour : solvent-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : not determined

Boiling point/boiling range : 176 °F / 80 °C  
(1013 hPa)

Flash point : -5 °C  
Method: Tag open cup


Evaporation rate : 1  
Ethyl Ether = 1

Upper explosion limit : 12.0 %(V)

Lower explosion limit : 2.0 %(V)

Vapour pressure : 71.0000 mmHg (68.00 °F)

Relative vapour density : 2.5(Air = 1.0)

 <b>BOSTIK</b>	Page: 11
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
	SDS Number: R0171288
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	Version: 3.1

Relative density : 0.8629 (25 °C)

Density : 0.8629 g/cm<sup>3</sup> (25 °C)

Solubility(ies)  
Water solubility : not determined

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : not determined

Thermal decomposition : No data available

Viscosity  
Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Oxidizing properties : Not applicable

---

## SECTION 10. STABILITY AND REACTIVITY


Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.

Conditions to avoid : excessive heat  
Heat, flames and sparks.

Incompatible materials : 1,3-butadiene  
ammonium salts  
aluminum  
aluminum salts  
Amines  
Copper  
Copper alloys  
halogenated hydrocarbons  
halogens  
Iron

 <b>BOSTIK</b>	Page: 12
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

Lead  
magnesium  
strong alkalis  
strong mineral acids  
Strong oxidizing agents  
Zinc

Hazardous decomposition products

Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
calcium oxide  
Hydrocarbons  
Acetone

---

## SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye contact  
Ingestion

### Acute toxicity

Not classified based on available information.

#### Components:

##### METHYL ETHYL KETONE:

Acute oral toxicity : LD50 (Rat): 2,300 - 3,500 mg/kg


Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

##### CALCIUM CARBONATE:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: No adverse effect has been observed in acute oral toxicity tests.

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402

 <b>BOSTIK</b>	Page: 13
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

Assessment: Not classified as acutely toxic by dermal absorption under GHS.

**PHENOL:**

Acute oral toxicity : LD50 (Rat): 317 mg/kg

LD50 (Mouse): 270 mg/kg

Assessment: The component/mixture is classified as acute oral toxicity, category 3.

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute inhalation toxicity, category 3.

Acute dermal toxicity : LD50 (Rabbit): 850 mg/kg

LD50 (Rat, females): 660 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation and/or dermatitis.

**Components:**

**METHYL ETHYL KETONE:**

Result: No skin irritation

**CALCIUM CARBONATE:**

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

**PHENOL:**

Result: Corrosive to skin

**Serious eye damage/eye irritation**

Causes serious eye irritation.


**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

**Components:**

**METHYL ETHYL KETONE:**

Result: Irritating to eyes.

 <b>BOSTIK</b>	Page: 14
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

**CALCIUM CARBONATE:**  
Species: Rabbit  
Result: Slight, transient irritation  
Method: OECD Test Guideline 405

**PHENOL:**  
Result: Corrosive

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.  
Respiratory sensitisation: Not classified based on available information.

**Components:**

**CALCIUM CARBONATE:**  
Test Type: Local lymph node assay  
Species: Mouse  
Assessment: Did not cause sensitisation on laboratory animals.  
Method: OECD Test Guideline 429  
Result: Did not cause sensitisation on laboratory animals.

**PHENOL:**  
Test Type: Buehler Test  
Exposure routes: Dermal  
Species: Guinea pig  
Assessment: Did not cause sensitisation on laboratory animals.  
Method: OECD Test Guideline 406


Exposure routes: Dermal  
Species: Mouse  
Assessment: Did not cause sensitisation on laboratory animals.  
Result: negative

Germ cell mutagenicity  
Suspected of causing genetic defects.

**Components:**

**CALCIUM CARBONATE:**  
Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Test species: Human lymphocytes  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 473  
Result: negative

**PHENOL:**  
Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Test species: Chinese hamster ovary cells  
Metabolic activation: with metabolic activation  
Method: OECD Test Guideline 473  
Result: positive

 <b>BOSTIK</b>	Page: 15
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

: Test Type: Micronucleus test  
Test species: Chinese hamster ovary cells  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 487  
Result: positive

Genotoxicity in vivo : Test Type: Micronucleus test  
Test species: Mouse (male and female)  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: positive

Germ cell mutagenicity- Assessment : In vitro tests showed mutagenic effects

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

May cause drowsiness or dizziness.

**Components:**

**METHYL ETHYL KETONE:**

Assessment: May cause drowsiness or dizziness.

**STOT - repeated exposure**

May cause damage to organs (Skin, Nervous system, Liver, Kidney) through prolonged or repeated exposure.

**Components:**

**PHENOL:**

Target Organs: Skin

Assessment: May cause damage to organs through prolonged or repeated exposure.

Target Organs: Nervous system

Assessment: May cause damage to organs through prolonged or repeated exposure.

Target Organs: Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

Target Organs: Kidney


Assessment: May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

 <b>BOSTIK</b>	Page: 16
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

**Components:**

METHYL ETHYL KETONE:

May be harmful if swallowed and enters airways.

**Further information****Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**Components:**

METHYL ETHYL KETONE:

Remarks: Central nervous system

PHENOL:

Remarks: Central nervous system

Remarks: Blood

**Carcinogenicity:****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Acute aquatic toxicity Category 3; Harmful to aquatic life.


Long-term (chronic) aquatic hazard : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

**Components:**

METHYL ETHYL KETONE:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 3,130 - 3,320



 <b>BOSTIK</b>	Page: 17
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

mg/l  
 Exposure time: 96 h  
 Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4,025 - 6,440 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Remarks: Intoxication

**CALCIUM CARBONATE:**  
 Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): > 56,000 mg/l  
 Exposure time: 96 h  
 Test Type: static test

**PHENOL:**  
 Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 7.5 - 14 mg/l  
 Exposure time: 96 h  
 Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 67.5 mg/l  
 Exposure time: 96 h  
 Test Type: flow-through test

LC50 (Danio rerio (zebra fish)): 27.8 mg/l  
 Exposure time: 96 h  
 Method: static test  
 Remarks: mortality

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 3.1 mg/l  
 Exposure time: 48 h  
 Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 61.1 mg/l  
 Exposure time: 96 h  
 Test Type: static test


Toxicity to fish (Chronic toxicity) : NOEC (Fish): 0.077 mg/l  
 Exposure time: 60 d  
 Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.16 mg/l  
 Exposure time: 16 d  
 Test Type: semi-static test

**Persistence and degradability**

**Components:**

PHENOL:

 <b>BOSTIK</b>	Page: 18
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
	SDS Number: R0171288
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	Version: 3.1

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 62 %  
Exposure time: 100 h  
Method: OECD Test Guideline 301C

No data available

**Bioaccumulative potential**

**Components:**

METHYL ETHYL KETONE:

Partition coefficient: n-octanol/water : log Pow: 0.29

PHENOL:

Partition coefficient: n-octanol/water : log Pow: 1.46

No data available

**Mobility in soil**

**Components:**

PHENOL:

Distribution among environmental compartments : Medium: Soil  
Koc: > 14 - < 73Method: OECD Test Guideline 121

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

**Components:**

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**


General advice : Dispose of in accordance with all applicable local, state and federal regulations.

The product should not be allowed to enter drains, water courses or the soil.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Empty containers should be taken to an approved waste

		Page: 19
<b>SAFETY DATA SHEET</b>		Revision Date: 05/16/2022
		Print Date: 12/6/2023
		SDS Number: R0171288
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497		Version: 3.1

handling site for recycling or disposal.  
 Do not re-use empty containers.  
 Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14. TRANSPORT INFORMATION

### International transport regulations

#### REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

#### U.S. DOT - ROAD

UN	1133	Adhesives	3	II	
----	------	-----------	---	----	--

#### CFR\_RAIL\_C

UN	1133	Adhesives	3	II	
----	------	-----------	---	----	--

#### U.S. DOT - INLAND WATERWAYS

UN	1133	Adhesives	3	II	
----	------	-----------	---	----	--

#### TDG\_ROAD\_C

UN	1133	ADHESIVES	3	II	
----	------	-----------	---	----	--

#### TDG\_RAIL\_C

UN	1133	ADHESIVES	3	II	
----	------	-----------	---	----	--

#### TDG\_INWT\_C

UN	1133	ADHESIVES	3	II	
----	------	-----------	---	----	--


#### INTERNATIONAL MARITIME DANGEROUS GOODS

UN	1133	ADHESIVES	3	II	
----	------	-----------	---	----	--

#### INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN	1133	Adhesives	3	II	
----	------	-----------	---	----	--

#### INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

		Page: 20
<b>SAFETY DATA SHEET</b>		Revision Date: 05/16/2022
		Print Date: 12/6/2023
		SDS Number: R0171288
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497		Version: 3.1

UN	1133	Adhesives	3	II
----	------	-----------	---	----

**MX DG**

UN	1133	ADHESIVES	3	II
----	------	-----------	---	----

**\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**TSCA list**

No substances are subject to TSCA 12(b) export notification requirements.

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
METHYL ETHYL KETONE	78-93-3	5000	6511

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ORTHO CRESOL	95-48-7	100	36764

**SARA 311/312 Hazards**


: Flammable (gases, aerosols, liquids, or solids)  
 Skin corrosion or irritation  
 Serious eye damage or eye irritation  
 Germ cell mutagenicity  
 Specific target organ toxicity (single or repeated exposure)

**SARA 302**

: PHENOL 108-95-2 1.08 %

**SARA 313**

The following components are subject to reporting levels established by SARA Title III, Section 313:

 <b>BOSTIK</b>	Page: 21
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
	SDS Number: R0171288
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	Version: 3.1

PHENOL

108-95-2

1.08 %

**California Prop. 65**

WARNING: This product can expose you to chemicals including formaldehyde, 4-vinylcyclohexene, acrylonitrile, 1,3-butadiene, which is/are known to the State of California to cause cancer, and 4-vinylcyclohexene, 1,3-butadiene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : On the inventory, or in compliance with the inventory
- TSCA : On or in compliance with the active portion of the TSCA inventory


**Inventories**

AIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)


---

**SECTION 16. OTHER INFORMATION**


**Further information**

	Page: 22
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
	SDS Number: R0171288
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	Version: 3.1

**NFPA 704:**



**HMIS® IV:**




HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of H-Statements**

- H225                      Highly flammable liquid and vapor.
- H301                      Toxic if swallowed.
- H311                      Toxic in contact with skin.
- H314                      Causes severe skin burns and eye damage.
- H318                      Causes serious eye damage.
- H319                      Causes serious eye irritation.
- H331                      Toxic if inhaled.
- H336                      May cause drowsiness or dizziness.
- H341                      Suspected of causing genetic defects.
- H373                      May cause damage to organs through prolonged or repeated exposure.

**Full text of other abbreviations**

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and

 <b>BOSTIK</b>	Page: 23
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
	SDS Number: R0171288
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	Version: 3.1


Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

This sds has been prepared by Bostik. (<http://www.Bostik.com>)

Sources of key data used to compile the Safety Data Sheet : Bostik internal data including own and sponsored test reports  
European Union Law with content from the Official Journal of the European Union.  
European Chemicals Agency; the EU authority implementing the EU's chemicals legislation for companies.  
The German Water Hazard Classes.  
ReachCentrum; a series of support services to help comply with REACH regulations.  
The European Commission; proposing legislation, administering and implementing EU policies, and enforcing EU law.  
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.  
Cefic, the European Chemical Industry Council.  
ESIS European Chemical Substances Information System

Revision Date : 05/16/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

 <b>BOSTIK</b>	Page: 24
<b>SAFETY DATA SHEET</b>	Revision Date: 05/16/2022
	Print Date: 12/6/2023
Pliobond™ 20 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 162497	SDS Number: R0171288 Version: 3.1

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.  
US / EN