 BOSTIK	Page: 1
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	SDS Number: R0381726 Version: 3.0

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Pliobond™ 35
ADHESIVE
™ Trademark, Bostik or its subsidiaries, registered in various countries

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Adhesives


Details of the supplier of the safety data sheet Bostik, Inc. 11320 W Watertown Plank Road Wauwatosa, WI 53226 United States of America (USA) +1 (800) 843-0844 (Domestic Toll Free); +1 (414) 774-2250 (International) EHSproductsafety.US@bostik.com	Emergency telephone number Chemtrec 1-800-424-9300, outside US 1-703-527-3887 Regulatory information Rocky Mountain Poison center: 1-866-767-5089
---	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2
Eye irritation : Category 2A
Skin sensitization : Category 1
Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure

GHS label elements

 BOSTIK	Page: 2
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	SDS Number: R0381726 Version: 3.0

Hazard pictograms :



Signal Word :

Danger

Hazard Statements :

Highly flammable liquid and vapor.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Precautionary Statements :

Prevention:
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/ eye protection/ face protection.

Response:
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If skin irritation or rash occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Wash contaminated clothing before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:
Dispose of contents/ container to an approved waste disposal plant.



BOSTIK

SAFETY DATA SHEET

Revision Date: 03/04/2022

Print Date: 12/6/2023

SDS Number: R0381726

Version: 3.0

Pliobond™ 35 ADHESIVE
™ Trademark, Bostik or its subsidiaries, registered in various countries
167510

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture


Chemical nature : Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
ACETONE	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	62.216
METHYL ETHYL KETONE	78-93-3	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	7.008
CALCIUM CARBONATE	471-34-1	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	3.8057
BENZOTHAIZYL DISULFIDE	120-78-5	Skin Sens. 1; H317	0.121

SECTION 4. FIRST AID MEASURES


General advice : Move out of dangerous area.
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
Show this safety data sheet to the doctor in attendance.

 BOSTIK	Page: 4
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	SDS Number: R0381726 Version: 3.0

Do not leave the victim unattended.

- If inhaled : Move to fresh air.
If unconscious, place in recovery position and seek medical advice.
Consult a physician after significant exposure.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
Wash contaminated clothing before re-use.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.
Ingestion of large amounts or other significant exposure to this material (or a component) may cause alkalosis.
Excessive calcium intake may cause gastrointestinal symptoms, hypertension, hypercalcemia, kidney stones, and may inhibit absorption of iron, zinc, and possibly other trace elements.
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause drowsiness or dizziness.
- Notes to physician : No hazards which require special first aid measures.


SECTION 5. FIREFIGHTING MEASURES

 BOSTIK	Page: 5
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	SDS Number: R0381726 Version: 3.0

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Nitrogen oxides (NO_x)
Hydrogen cyanide (hydrocyanic acid)
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES


- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Use personal protective equipment.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

 BOSTIK	Page: 6
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	SDS Number: R0381726 Version: 3.0

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Keep away from open flames, hot surfaces and sources of ignition.
Use only explosion-proof equipment.
- Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
- Advice on safe handling : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Container hazardous when empty.
Take precautionary measures against static discharges.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

 BOSTIK	Page: 7
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
	SDS Number: R0381726
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	Version: 3.0

Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ACETONE	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		C	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
		METHYL ETHYL KETONE	78-93-3	TWA
STEL	300 ppm			ACGIH
TWA	200 ppm 590 mg/m3			NIOSH REL
ST	300 ppm 885 mg/m3			NIOSH REL
TWA	200 ppm 590 mg/m3			OSHA Z-1
TWA	200 ppm 590 mg/m3			OSHA P0



BOSTIK

SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
	SDS Number: R0381726
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	Version: 3.0

		STEL	300 ppm 885 mg/m3	OSHA P0
		PEL	200 ppm 590 mg/m3	CAL PEL
		STEL	300 ppm 885 mg/m3	CAL PEL
CALCIUM CARBONATE	471-34-1	PEL	10 mg/m3 Total dust	CAL PEL
		PEL	5 mg/m3 respirable dust fraction	CAL PEL
		TWA	5 mg/m3 Respirable (Calcium carbonate)	NIOSH REL
		TWA	10 mg/m3 total (Calcium carbonate)	NIOSH REL


Hazardous components without workplace control parameters

Components	CAS-No.
BENZOTHIAZYL DISULFIDE	120-78-5

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
ACETONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ZUS_A CGIHB
METHYL ETHYL KETONE	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ZUS_A CGIHB

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

 BOSTIK	Page: 9
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	SDS Number: R0381726 Version: 3.0

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter within the capabilities of the respirator/filter combination.
Where concentrations are above recommended limits or are unknown, or a cartridge type respirator is not adequate, wear a positive-pressure supplied-air respirator.
- Hand protection
- Material : butyl-rubber
- Break through time : 480 min
- Glove thickness : > 0.5 mm
- Remarks : The exact break through time can be obtained from the protective glove producer and this has to be observed. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.
- Skin and body protection : Wear resistant gloves (consult your safety equipment supplier).
Wear as appropriate:
Impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
- Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Physical state : liquid
- Colour : tan
- Odour : No information available.
- Odour Threshold : No data available



BOSTIK

SAFETY DATA SHEET

Revision Date: 03/04/2022

Print Date: 12/6/2023


SDS Number: R0381726

Version: 3.0

Pliobond™ 35 ADHESIVE
™ Trademark, Bostik or its subsidiaries, registered in various countries
167510

pH	: No data available
Melting point/freezing point	: not determined
Boiling point/boiling range	: not determined
Flash point	: < -7 °C Method: Seta closed cup
Evaporation rate	: not determined
Flammability (liquids)	: not determined
Upper explosion limit	: Upper explosion limit not determined
Lower explosion limit	: Lower explosion limit not determined
Vapour pressure	: not determined
Relative vapour density	: < 1(Air = 1.0)
Relative density	: 0.89 (77.00 °F)
Density	: 0.89 g/cm ³ (77.00 °F)
Solubility(ies)	
Water solubility	: not determined
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: not determined
Viscosity, kinematic	: not determined
Oxidizing properties	: Not applicable

SECTION 10. STABILITY AND REACTIVITY

 BOSTIK	Page: 11
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	SDS Number: R0381726 Version: 3.0

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids
alkalis
ammonium salts
aluminum salts
Amines
Ammonia
Copper
Copper alloys
halogens
peroxides
Reducing agents
strong alkalis
Strong oxidizing agents

Hazardous decomposition products : Carbon dioxide (CO₂)
Carbon monoxide
calcium oxide
Hydrocarbons
Acetone

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity


Not classified based on available information.

Components:

ACETONE:

Acute oral toxicity : LD50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 76 mg/l
Exposure time: 4 h

 BOSTIK	Page: 12
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	SDS Number: R0381726 Version: 3.0

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 7,426 mg/kg

METHYL ETHYL KETONE:

Acute oral toxicity : LD50 (Rat): 2,300 - 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

CALCIUM CARBONATE:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: No adverse effect has been observed in acute oral toxicity tests.

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

BENZOTHIAZYL DISULFIDE:

Acute oral toxicity : LD50 (Rat): > 12 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 7,940 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.


Remarks: May cause skin irritation in susceptible persons.

Components:

ACETONE:

Result: Slight, transient irritation

Result: Repeated exposure may cause skin dryness or cracking.

 BOSTIK	Page: 13
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	SDS Number: R0381726 Version: 3.0

METHYL ETHYL KETONE:
Result: No skin irritation

CALCIUM CARBONATE:
Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

BENZOTHIAZYL DISULFIDE:
Result: Slight, transient irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

ACETONE:
Result: Irritating to eyes.

METHYL ETHYL KETONE:
Result: Irritating to eyes.

CALCIUM CARBONATE:
Species: Rabbit
Result: Slight, transient irritation
Method: OECD Test Guideline 405

BENZOTHIAZYL DISULFIDE:
Result: Slight, transient irritation

Respiratory or skin sensitisation


Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:

CALCIUM CARBONATE:
Test Type: Local lymph node assay
Species: Mouse
Assessment: Did not cause sensitisation on laboratory animals.
Method: OECD Test Guideline 429
Result: Did not cause sensitisation on laboratory animals.

BENZOTHIAZYL DISULFIDE:
Assessment: May cause sensitisation by skin contact.

 BOSTIK	Page: 14
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	SDS Number: R0381726 Version: 3.0

Germ cell mutagenicity
Not classified based on available information.

Components:

CALCIUM CARBONATE:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Test species: Human lymphocytes
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

ACETONE:

Exposure routes: Inhalation
Target Organs: Nervous system
Assessment: May cause drowsiness or dizziness.

METHYL ETHYL KETONE:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

ACETONE:

May be harmful if swallowed and enters airways.

METHYL ETHYL KETONE:

May be harmful if swallowed and enters airways.

Further information


Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

METHYL ETHYL KETONE:

Remarks: Central nervous system

	Page: 15
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	SDS Number: R0381726 Version: 3.0

**Carcinogenicity:
IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard

: Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic hazard

: Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

ACETONE:

Toxicity to fish

: LC50 (Oncorhynchus mykiss (rainbow trout)): 4,740 - 6,330 mg/l

Exposure time: 96 h

Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,733 - 9,482 mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to algae

: NOEC (Microcystis aeruginosa (blue-green algae)): 530 mg/l

Exposure time: 8 d

Test Type: static test


Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 2,112 mg/l

Exposure time: 28 d

Test Type: flow-through test

METHYL ETHYL KETONE:

 BOSTIK	Page: 16
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	SDS Number: R0381726 Version: 3.0

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 3,130 - 3,320 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4,025 - 6,440 mg/l
Exposure time: 48 h
Test Type: static test
Remarks: Intoxication

CALCIUM CARBONATE:

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): > 56,000 mg/l
Exposure time: 96 h
Test Type: static test

Persistence and degradability

Components:

ACETONE:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90.9 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

No data available

Bioaccumulative potential

Components:

ACETONE:

Partition coefficient: n-octanol/water : log Pow: -0.24

METHYL ETHYL KETONE:

Partition coefficient: n-octanol/water : log Pow: 0.29

No data available

Mobility in soil

Components:

No data available


Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

Components:

		Page: 17
SAFETY DATA SHEET		Revision Date: 03/04/2022
		Print Date: 12/6/2023
		SDS Number: R0381726
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510		Version: 3.0

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

The product should not be allowed to enter drains, water courses or the soil.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

UN	1133	Adhesives	3	II	
----	------	-----------	---	----	--

CFR_RAIL_C

UN	1133	Adhesives	3	II	
----	------	-----------	---	----	--


U.S. DOT - INLAND WATERWAYS

UN	1133	Adhesives	3	II	
----	------	-----------	---	----	--

TDG_ROAD_C

UN	1133	ADHESIVES	3	II	
----	------	-----------	---	----	--

TDG_RAIL_C

	Page: 18
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
	SDS Number: R0381726
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	Version: 3.0

UN 1133 ADHESIVES	3	II
-------------------	---	----

TDG INWT C

UN 1133 ADHESIVES	3	II
-------------------	---	----

INTERNATIONAL MARITIME DANGEROUS GOODS

UN 1133 ADHESIVES	3	II
-------------------	---	----

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN 1133 Adhesives	3	II
-------------------	---	----

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN 1133 Adhesives	3	II
-------------------	---	----

MX_DG

UN 1133 ADHESIVES	3	II
-------------------	---	----

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION


TSCA list

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ACETONE	67-64-1	5000	8036

		Page: 19
SAFETY DATA SHEET		Revision Date: 03/04/2022
		Print Date: 12/6/2023
		SDS Number: R0381726
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510		Version: 3.0

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ORTHO CRESOL	95-48-7	100	31635

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
 Serious eye damage or eye irritation
 Respiratory or skin sensitisation
 Specific target organ toxicity (single or repeated exposure)

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.


California Prop. 65

WARNING: This product can expose you to chemicals including benzene, formaldehyde, 4-vinylcyclohexene, acrylonitrile, 1,3-butadiene, which is/are known to the State of California to cause cancer, and benzene, 4-vinylcyclohexene, 1,3-butadiene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : On the inventory, or in compliance with the inventory
- TSCA : On or in compliance with the active portion of the TSCA inventory

Inventories


		Page: 20
SAFETY DATA SHEET		Revision Date: 03/04/2022
		Print Date: 12/6/2023
		SDS Number: R0381726
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510		Version: 3.0

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		


HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of H-Statements

H225	Highly flammable liquid and vapor.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -


 BOSTIK	Page: 21
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
	SDS Number: R0381726
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	Version: 3.0

Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

This sds has been prepared by Bostik. (<http://www.Bostik.com>)

Sources of key data used to compile the Safety Data Sheet : Bostik internal data including own and sponsored test reports
European Union Law with content from the Official Journal of the European Union.
European Chemicals Agency; the EU authority implementing the EU's chemicals legislation for companies.
The German Water Hazard Classes.
ReachCentrum; a series of support services to help comply with REACH regulations.
The European Commission; proposing legislation, administering and implementing EU policies, and enforcing EU law.
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.
Cefic, the European Chemical Industry Council.
ESIS European Chemical Substances Information System

Revision Date : 03/04/2022

	Page: 22
SAFETY DATA SHEET	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ 35 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 167510	SDS Number: R0381726 Version: 3.0

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN