 <b>BOSTIK</b>		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 03/04/2022
		Print Date: 12/6/2023
		SDS Number: R0171291
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703		Version: 3.0

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : Pliobond™ HT30  
ADHESIVE  
™ Trademark, Bostik or its subsidiaries, registered in various countries

### Relevant identified uses of the substance or mixture and uses advised against


Recommended use : ADHESIVE

<b>Details of the supplier of the safety data sheet</b> Bostik, Inc. 11320 W Watertown Plank Road Wauwatosa, WI 53226 United States of America (USA) +1 (800) 843-0844 (Domestic Toll Free); +1 (414) 774-2250 (International)  EHSproductsafety.US@bostik.com	<b>Emergency telephone number</b> Chemtrec 1-800-424-9300, outside US 1-703-527-3887  <b>Regulatory information</b> Rocky Mountain Poison center: 1-866-767-5089
---	--

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Flammable liquids : Category 2  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Skin sensitization : Category 1  
Germ cell mutagenicity : Category 2  
Carcinogenicity : Category 1B  
Reproductive toxicity : Category 1B  
Specific target organ toxicity : Category 3 (Central nervous system)

	Page: 2
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

- single exposure

Specific target organ toxicity : Category 2 (Skin, Nervous system, Liver, Kidney)  
- repeated exposure


**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : Highly flammable liquid and vapor.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of causing genetic defects.  
May cause cancer.  
May damage the unborn child.  
May cause damage to organs (Skin, Nervous system, Liver, Kidney) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe mist or vapors.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel

	Page: 3
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/ attention.

If skin irritation or rash occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
METHYL ETHYL KETONE	78-93-3	Flam. Liq. 2; H225  Eye Irrit. 2A; H319  STOT SE 3; H336	56.131
ISOPROPANOL	67-63-0	Flam. Liq. 2; H225  Eye Irrit. 2A; H319  STOT SE 3; H336	12.133
Amorphous silica	7631-86-9	This material is not considered hazardous under the OSHA	2.174



# BOSTIK

## SAFETY DATA SHEET

Revision Date: 03/04/2022

Print Date: 12/6/2023

SDS Number: R0171291


Version: 3.0

Pliobond™ HT30 ADHESIVE  
™ Trademark, Bostik or its subsidiaries, registered in various countries  
133703

		Hazard Communication Standard (HazCom 2012).	
PHENOL	108-95-2	Comb Dust Acute Tox. 3; H301  Acute Tox. 3; H331  Acute Tox. 3; H311  Skin Corr. 1; H314  Eye Dam. 1; H318  Muta. 2; H341  STOT RE 2; H373	1.3188
FORMALDEHYDE	50-00-0	Flam. Liq. 4; H227  Acute Tox. 3; H301  Acute Tox. 2; H330  Acute Tox. 3; H311  Skin Corr. 1B; H314  Eye Dam. 1; H318  Skin Sens. 1A; H317  Muta. 2; H341  Carc. 1B; H350	0.2638


### SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.

 <b>BOSTIK</b>	Page: 5
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

- If inhaled : Move to fresh air.  
If unconscious, place in recovery position and seek medical advice.  
Consult a physician after significant exposure.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.
- If swallowed : Obtain medical attention.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Do not induce vomiting. Phenol concentrations greater than 1.5% produce irritation and greater than 5% are corrosive; vomiting can cause further damage to the mouth and throat.  
Do not dilute the swallowed material, since this may enhance its absorption. Seek immediate medical attention. If possible, do not leave the individual unattended. Vomiting and diarrhea may occur spontaneously.
- Most important symptoms and effects, both acute and delayed : Administration of high doses of isopropanol in combination with known hepatotoxic chemicals resulted in enhanced liver toxicity in experimental animals.  
Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.  
Pulmonary edema may be delayed.  
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)  
Cough  
Headache  
low body temperature  
confusion

 <b>BOSTIK</b>	Page: 6
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

irregular heartbeat  
cyanosis (causes blue coloring of the skin and nails from lack of oxygen)  
lung edema (fluid buildup in the lung tissue)  
Convulsions  
respiratory failure  
Difficulty in breathing  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of causing genetic defects.  
May cause cancer.  
May damage the unborn child.  
May cause damage to organs through prolonged or repeated exposure.


Notes to physician

: Phenol adsorbs to activated charcoal, and it maybe preferable to ipecac-induced emesis because seizures or coma may onset rapidly and because of the corrosive effects of phenol. A usual activated charcoal dose in adults is 30-100 g and in children is 15-30 g. Activated charcoal should be administered with, or followed by, a cathartic. If endoscopy is planned, charcoal may obscure visualization of affected areas. Gastric lavage may be indicated if it is performed soon after ingestion or in patients who are comatose or at risk of seizures. Monitor for seizures, metabolic acidosis and ventricular dysrhythmias.

---

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Alcohol-resistant foam  
Carbon dioxide (CO2)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

 <b>BOSTIK</b>	Page: 7
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0


Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not allow run-off from fire fighting to enter drains or water courses.

- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Nitrogen oxides (NO<sub>x</sub>)  
Hydrogen cyanide (hydrocyanic acid)  
Organic acids
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- Other information : Comply with all applicable federal, state, and local regulations.  
Suppress (knock down) gases/vapours/mists with a water spray jet.

 <b>BOSTIK</b>	Page: 8
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

---

## SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
No sparking tools should be used.  
Keep away from open flames, hot surfaces and sources of ignition.  
Use only explosion-proof equipment.
- Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
- Advice on safe handling : Open drum carefully as content may be under pressure.  
Avoid formation of aerosol.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Container hazardous when empty.  
Take precautionary measures against static discharges.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
No smoking.
- Further information on storage stability : No decomposition if stored and applied as directed.





**BOSTIK**

**SAFETY DATA SHEET**

Revision Date: 03/04/2022

Print Date: 12/6/2023

SDS Number: R0171291

Version: 3.0

Pliobond™ HT30 ADHESIVE  
 ™ Trademark, Bostik or its subsidiaries, registered in various countries  
 133703

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
METHYL ETHYL KETONE	78-93-3	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m3	NIOSH REL
		ST	300 ppm 885 mg/m3	NIOSH REL
		TWA	200 ppm 590 mg/m3	OSHA Z-1
		TWA	200 ppm 590 mg/m3	OSHA P0
		STEL	300 ppm 885 mg/m3	OSHA P0
		PEL	200 ppm 590 mg/m3	CAL PEL
		STEL	300 ppm 885 mg/m3	CAL PEL
		ISOPROPANOL	67-63-0	TWA
STEL	400 ppm			ACGIH
TWA	400 ppm 980 mg/m3			NIOSH REL
ST	500 ppm 1,225 mg/m3			NIOSH REL
TWA	400 ppm 980 mg/m3			OSHA Z-1
TWA	400 ppm 980 mg/m3			OSHA P0
STEL	500 ppm 1,225 mg/m3			OSHA P0
PEL	400 ppm 980 mg/m3			CAL PEL
STEL	500 ppm 1,225 mg/m3			CAL PEL
Amorphous silica	7631-86-9			TWA




# BOSTIK

<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
	SDS Number: R0171291
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	Version: 3.0

		TWA	80 mg/m3 / %SiO2 Dust (Silica)	OSHA Z-3
		TWA	6 mg/m3 (Silica)	NIOSH REL
		PEL	6 mg/m3	CAL PEL
PHENOL	108-95-2	TWA	5 ppm	ACGIH
		TWA	5 ppm 19 mg/m3	NIOSH REL
		C	15.6 ppm 60 mg/m3	NIOSH REL
		TWA	5 ppm 19 mg/m3	OSHA Z-1
		TWA	5 ppm 19 mg/m3	OSHA P0
		PEL	5 ppm 19 mg/m3	CAL PEL
FORMALDEHYDE	50-00-0	TWA	0.016 ppm	NIOSH REL
		C	0.1 ppm	NIOSH REL
		PEL	0.75 ppm	OSHA CARC
		STEL	2 ppm	OSHA CARC
		PEL	0.75 ppm	CAL PEL
		STEL	2 ppm	CAL PEL
		TWA	0.016 ppm (Formaldehyde)	NIOSH REL
		C	0.1 ppm (Formaldehyde)	NIOSH REL
		TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
METHYL ETHYL KETONE	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ZUS_A CGIHB
ISOPROPANOL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ZUS_A CGIHB
PHENOL	108-95-2	Phenol	Urine	End of	250 mg/g	ZUS_A

	Page: 11
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
	SDS Number: R0171291
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	Version: 3.0

				shift (As soon as possible after exposure ceases)	Creatinine	CGIHB
--	--	--	--	---	------------	-------

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

**Respiratory protection** : In the case of vapour formation use a respirator with an approved filter within the capabilities of the respirator/filter combination.  
Where concentrations are above recommended limits or are unknown, or a cartridge type respirator is not adequate, wear a positive-pressure supplied-air respirator.

**Hand protection**

**Material** : butyl-rubber  
**Break through time** : 480 min  
**Glove thickness** : > 0.5 mm

**Remarks** : The exact break through time can be obtained from the protective glove producer and this has to be observed. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.  
The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**Eye protection** : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

**Skin and body protection** : Wear resistant gloves (consult your safety equipment supplier).  
Wear as appropriate:  
Impervious clothing  
Safety shoes  
Flame-resistant clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Discard gloves that show tears, pinholes, or signs of wear.

**Hygiene measures** : Wash hands before breaks and at the end of workday.  
When using do not eat or drink.  
When using do not smoke.



# BOSTIK

**SAFETY DATA SHEET**

Revision Date: 03/04/2022

Print Date: 12/6/2023


SDS Number: R0171291

Version: 3.0

Pliobond™ HT30 ADHESIVE  
™ Trademark, Bostik or its subsidiaries, registered in  
various countries  
133703

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: liquid
Physical state	: liquid
Colour	: pink
Odour	: characteristic, pungent
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: not determined
Boiling point/boiling range	: 176 °F / 80 °C (1013 hPa)
Flash point	: -3 °C Method: Seta closed cup
Evaporation rate	: > 1 Ethyl Ether = 1
Upper explosion limit	: 12 %(V) Calculated Explosive Limit
Lower explosion limit	: 2 %(V) Calculated Explosive Limit
Vapour pressure	: 70.0000 mmHg (68.00 °F)
Relative vapour density	: 2.5(Air = 1.0)
Relative density	: 0.891 (77.00 °F)
Density	: 0.891 g/cm <sup>3</sup> (77.00 °F)
Solubility(ies)	
Water solubility	: partly soluble
Solubility in other solvents	: No data available

 <b>BOSTIK</b>	Page: 13
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

Partition coefficient: n-octanol/water : not determined

Thermal decomposition : No data available

Viscosity

    Viscosity, dynamic : not determined

    Viscosity, kinematic : not determined

Oxidizing properties : Not applicable

---

#### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.


Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air. Formaldehyde reacts with peroxides, phenol, strong acids, amines and strong oxidizing agents. Formaldehyde reacts violently with nitrogen dioxide, nitromethane, perchloric acid, perchloric acid-aniline mixtures, or peroxyformic acid to yield explosive compounds. It reacts with hydrochloric acid or to organic chlorides to form the carcinogen, bis(chloromethyl)ether.

Conditions to avoid : excessive heat

Heat, flames and sparks.

Incompatible materials : 1,3-butadiene  
Acids  
Aldehydes  
alkalis  
aluminum  
Amines  
Copper  
Copper alloys  
Ethylene oxide  
fluorides  
halogenated hydrocarbons  
halogens  
Iron  
isocyanates  
Lead

 <b>BOSTIK</b>	Page: 14
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

magnesium  
strong alkalis  
Strong oxidizing agents  
Zinc  
Do not use with aluminum equipment at temperatures above 49C or 120 degrees F.

Hazardous decomposition products

Carbon monoxide  
Carbon dioxide (CO2)

---

## SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye contact  
Ingestion

### Acute toxicity

Not classified based on available information.

#### Components:

##### METHYL ETHYL KETONE:

Acute oral toxicity : LD50 (Rat): 2,300 - 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

##### ISOPROPANOL:

Acute oral toxicity : LD50 (Rat): 5.84 g/kg


Acute inhalation toxicity : LC50 (Rat): > 10000 ppm  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg

##### Amorphous silica:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l  
Exposure time: 4 h

 <b>BOSTIK</b>	Page: 15
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: yes  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**PHENOL:**

Acute oral toxicity : LD50 (Rat): 317 mg/kg

LD50 (Mouse): 270 mg/kg  
Assessment: The component/mixture is classified as acute oral toxicity, category 3.

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute inhalation toxicity, category 3.

Acute dermal toxicity : LD50 (Rabbit): 850 mg/kg

LD50 (Rat, females): 660 mg/kg

**FORMALDEHYDE:**

Acute oral toxicity : LD50 (Guinea pig): 260 mg/kg

LD50 (Rat): 100 mg/kg

LD50 (Rat, male): 800 mg/kg  
Assessment: The component/mixture is classified as acute oral toxicity, category 3.

Acute inhalation toxicity : LC50 (Rat): 588 mg/m<sup>3</sup>  
Exposure time: 4 h  
Test atmosphere: gas  
Assessment: The component/mixture is classified as acute inhalation toxicity, category 2.

Acute dermal toxicity : LD50 (Rabbit): 288 mg/kg


**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation and/or dermatitis.

 <b>BOSTIK</b>	Page: 16
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

**Components:**

**METHYL ETHYL KETONE:**

Result: No skin irritation

**ISOPROPANOL:**

Species: Rabbit

Result: No skin irritation

**Amorphous silica:**

Result: Slight, transient irritation

**PHENOL:**

Result: Corrosive to skin

**FORMALDEHYDE:**

Species: Rat

Exposure time: 40 min

Result: Corrosive after 3 minutes to 1 hour of exposure

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

**Components:**

**METHYL ETHYL KETONE:**

Result: Irritating to eyes.

**ISOPROPANOL:**

Species: Rabbit

Result: Irritating to eyes.

Method: OECD Test Guideline 405

**Amorphous silica:**

Result: Slight, transient irritation

**PHENOL:**

Result: Corrosive

**FORMALDEHYDE:**

Result: Corrosive


**Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

**Components:**



 <b>BOSTIK</b>	Page: 17
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
	SDS Number: R0171291
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	Version: 3.0

**ISOPROPANOL:**

Test Type: Buehler Test  
Species: Guinea pig  
Assessment: Does not cause skin sensitisation.  
Method: OECD Test Guideline 406

**PHENOL:**

Test Type: Buehler Test  
Exposure routes: Dermal  
Species: Guinea pig  
Assessment: Did not cause sensitisation on laboratory animals.  
Method: OECD Test Guideline 406

Exposure routes: Dermal  
Species: Mouse  
Assessment: Did not cause sensitisation on laboratory animals.  
Result: negative

**FORMALDEHYDE:**

Assessment: The product is a skin sensitiser, sub-category 1A.

Test Type: Maximisation Test  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: May cause sensitisation by skin contact.

Test Type: Buehler Test  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: May cause sensitisation by skin contact.


Test Type: Local lymph node assay  
Species: Mouse  
Method: OECD Test Guideline 429  
Result: Causes sensitisation.

Germ cell mutagenicity  
Suspected of causing genetic defects.

**Components:**

**ISOPROPANOL:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Test species: Chinese hamster ovary cells  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: negative

 <b>BOSTIK</b>	Page: 18
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

**PHENOL:**

- Genotoxicity in vitro
- : Test Type: Chromosome aberration test in vitro  
Test species: Chinese hamster ovary cells  
Metabolic activation: with metabolic activation  
Method: OECD Test Guideline 473  
Result: positive
  - : Test Type: Micronucleus test  
Test species: Chinese hamster ovary cells  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 487  
Result: positive


- Genotoxicity in vivo
- : Test Type: Micronucleus test  
Test species: Mouse (male and female)  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: positive

- Germ cell mutagenicity-Assessment
- : In vitro tests showed mutagenic effects

**FORMALDEHYDE:**

- Genotoxicity in vitro
- : Test Type: Ames test  
Test species: Salmonella typhimurium  
Metabolic activation: without metabolic activation  
Result: positive
  - : Test Type: Chromosome aberration test in vitro  
Test species: mouse lymphoma cells  
Metabolic activation: with and without metabolic activation  
Result: positive
  - : Test Type: In vitro mammalian cell gene mutation test  
Test species: Chinese hamster fibroblasts  
Metabolic activation: with and without metabolic activation  
Result: negative
  - : Test Type: in vitro assay  
Test species: Human lymphocytes  
Metabolic activation: with and without metabolic activation  
Result: Conflicting results have been seen in different studies.

- Genotoxicity in vivo
- : Test Type: Micronucleus test  
Test species: Mouse  
Application Route: Oral  
Result: negative

 <b>BOSTIK</b>	Page: 19
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

Test Type: Micronucleus test  
Test species: Mouse  
Application Route: inhalation (gas)  
Result: negative

Test Type: in vivo assay  
Test species: Rat  
Application Route: inhalation (gas)  
Result: negative

Test Type: Mouse specific locus test  
Test species: Mouse  
Application Route: inhalation (gas)  
Result: negative

Test Type: Mammalian bone marrow sister chromatid exchange  
Test species: Rat  
Application Route: inhalation (gas)  
Result: negative

Test Type: comet assay  
Test species: Rat  
Application Route: inhalation (gas)  
Result: negative

Germ cell mutagenicity-Assessment : In vitro tests showed mutagenic effects which were not observed with in vivo test.

**Carcinogenicity**

May cause cancer.

**Components:**

FORMALDEHYDE:

Species: Rat

Application Route: Ingestion

Result: negative

Species: Mouse

Application Route: Dermal


Result: negative

Species: Rat

Application Route: Inhalation

Result: positive

Carcinogenicity - Assessment : Presumed to have carcinogenic potential for humans

 <b>BOSTIK</b>	Page: 20
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

**Reproductive toxicity**

May damage the unborn child.

**Components:**

FORMALDEHYDE:

Effects on fertility : Remarks: No data available

Effects on foetal development : Species: Rat  
Result: No teratogenic effects

**STOT - single exposure**

May cause drowsiness or dizziness.

**Components:**

METHYL ETHYL KETONE:

Assessment: May cause drowsiness or dizziness.

ISOPROPANOL:

Assessment: May cause drowsiness or dizziness.

**STOT - repeated exposure**

May cause damage to organs (Skin, Nervous system, Liver, Kidney) through prolonged or repeated exposure.

**Components:**

PHENOL:

Target Organs: Skin

Assessment: May cause damage to organs through prolonged or repeated exposure.

Target Organs: Nervous system

Assessment: May cause damage to organs through prolonged or repeated exposure.

Target Organs: Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

Target Organs: Kidney

Assessment: May cause damage to organs through prolonged or repeated exposure.

**Repeated dose toxicity**

**Components:**

FORMALDEHYDE:

Species: Rat

No observed adverse effect level: 82 mg/kg

Application Route: Ingestion


Species: Rat

No observed adverse effect level: 1.2 mg/m<sup>3</sup>

Application Route: inhalation (gas)

Target Organs: Nose, Upper respiratory tract

**Aspiration toxicity**

 <b>BOSTIK</b>	Page: 21
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:**

METHYL ETHYL KETONE:

May be harmful if swallowed and enters airways.

**Further information**

**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**Components:**

METHYL ETHYL KETONE:

Remarks: Central nervous system

ISOPROPANOL:

Remarks: Central nervous system

PHENOL:

Remarks: Central nervous system

Remarks: Blood

**Carcinogenicity:**

**IARC**

Group 1: Carcinogenic to humans

FORMALDEHYDE 50-00-0

**OSHA**

OSHA specifically regulated carcinogen

FORMALDEHYDE 50-00-0

**NTP**

Known to be human carcinogen

FORMALDEHYDE 50-00-0

---

**SECTION 12. ECOLOGICAL INFORMATION**


**Ecotoxicity**

**Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic

: Acute aquatic toxicity Category 3; Harmful to aquatic life.

	Page: 22
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

hazard

Long-term (chronic) aquatic hazard : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

**Components:**

**METHYL ETHYL KETONE:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 3,130 - 3,320 mg/l  
 Exposure time: 96 h  
 Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4,025 - 6,440 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Remarks: Intoxication

**ISOPROPANOL:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l  
 Exposure time: 96 h  
 Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 24 h  
 Test Type: static test

**Amorphous silica:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10,000 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203  
 GLP: yes


**PHENOL:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 7.5 - 14 mg/l  
 Exposure time: 96 h  
 Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 67.5 mg/l  
 Exposure time: 96 h  
 Test Type: flow-through test

LC50 (Danio rerio (zebra fish)): 27.8 mg/l  
 Exposure time: 96 h  
 Method: static test  
 Remarks: mortality

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 3.1 mg/l  
 Exposure time: 48 h

 <b>BOSTIK</b>	Page: 23
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

- Test Type: static test
- Toxicity to algae : EC50 (*Pseudokirchneriella subcapitata* (green algae)): 61.1 mg/l  
Exposure time: 96 h  
Test Type: static test
- Toxicity to fish (Chronic toxicity) : NOEC (Fish): 0.077 mg/l  
Exposure time: 60 d  
Test Type: semi-static test
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Daphnia magna* (Water flea)): 0.16 mg/l  
Exposure time: 16 d  
Test Type: semi-static test
- FORMALDEHYDE:**  
Toxicity to fish : LC50 (*Striped bass* (*Morone saxatilis*)): 6.7 mg/l  
Exposure time: 96 h  
Method: static test
- Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 29 mg/l  
Exposure time: 48 h  
Method: Static  
Remarks: Intoxication
- EC50 (*Daphnia pulex* (Water flea)): 5.8 mg/l  
Exposure time: 48 h
- Toxicity to algae : ErC50 (*Desmodesmus subspicatus* (green algae)): 4.89 mg/l  
Exposure time: 72 h
- Toxicity to bacteria : EC50 (activated sludge): 19 mg/l  
Exposure time: 3 h  
Test Type: Respiration inhibition

**Persistence and degradability**


**Components:**

**PHENOL:**

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 62 %  
Exposure time: 100 h  
Method: OECD Test Guideline 301C

**FORMALDEHYDE:**

- Biodegradability : aerobic  
Result: Readily biodegradable.  
Biodegradation: 90 %  
Exposure time: 28 d

 <b>BOSTIK</b>	Page: 24
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

Method: OECD Test Guideline 301D

aerobic  
Result: Readily biodegradable.  
Biodegradation: > 90 %  
Exposure time: 2 Weeks  
Method: OECD Test Guideline 301C

Photodegradation :

No data available

**Bioaccumulative potential**

**Components:**

METHYL ETHYL KETONE:

Partition coefficient: n-octanol/water : log Pow: 0.29

ISOPROPANOL:

Partition coefficient: n-octanol/water : log Pow: 0.05

PHENOL:

Partition coefficient: n-octanol/water : log Pow: 1.46

FORMALDEHYDE:

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <= 4).

Partition coefficient: n-octanol/water : log Pow: 0.35 (25 °C)

No data available

**Mobility in soil**

**Components:**

PHENOL:

Distribution among environmental compartments : Medium: Soil  
Koc: > 14 - < 73 Method: OECD Test Guideline 121

No data available

**Other adverse effects**

**Product:**


Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

**Components:**

FORMALDEHYDE:

Results of PBT and vPvB : This substance is not considered to be persistent,



		Page: 25
<b>SAFETY DATA SHEET</b>		Revision Date: 03/04/2022
		Print Date: 12/6/2023
		SDS Number: R0171291
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703		Version: 3.0

assessment

bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

The product should not be allowed to enter drains, water courses or the soil.  
 Do not contaminate ponds, waterways or ditches with chemical or used container.  
 Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
 Dispose of as unused product.  
 Empty containers should be taken to an approved waste handling site for recycling or disposal.  
 Do not re-use empty containers.  
 Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14. TRANSPORT INFORMATION

#### International transport regulations

##### REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

#### U.S. DOT - ROAD


UN	1133	Adhesives	3	II	
----	------	-----------	---	----	--

#### CFR RAIL\_C

UN	1133	Adhesives	3	II	
----	------	-----------	---	----	--

#### U.S. DOT - INLAND WATERWAYS

UN	1133	Adhesives	3	II	
----	------	-----------	---	----	--

	Page: 26
	<b>SAFETY DATA SHEET</b>
	Revision Date: 03/04/2022
	Print Date: 12/6/2023
	SDS Number: R0171291
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	Version: 3.0

**TDG\_ROAD\_C**

UN	1133	ADHESIVES	3	II

**TDG\_RAIL\_C**

UN	1133	ADHESIVES	3	II

**TDG\_INWT\_C**

UN	1133	ADHESIVES	3	II

**INTERNATIONAL MARITIME DANGEROUS GOODS**

UN	1133	ADHESIVES	3	II

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

UN	1133	Adhesives	3	II

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

UN	1133	Adhesives	3	II

**MX\_DG**

UN	1133	ADHESIVES	3	II

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----


Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

		Page: 27
<b>SAFETY DATA SHEET</b>		Revision Date: 03/04/2022
		Print Date: 12/6/2023
		SDS Number: R0171291
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703		Version: 3.0

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
METHYL ETHYL KETONE	78-93-3	5000	8907

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ORTHO CRESOL	95-48-7	100	18957

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
 Skin corrosion or irritation  
 Serious eye damage or eye irritation  
 Respiratory or skin sensitisation  
 Germ cell mutagenicity  
 Carcinogenicity  
 Specific target organ toxicity (single or repeated exposure)  
 Reproductive toxicity

**SARA 302** : PHENOL 108-95-2 1.31 %


**SARA 313** The following components are subject to reporting levels established by SARA Title III, Section 313:

ISOPROPANOL	67-63-0	12.13 %
PHENOL	108-95-2	1.31 %
FORMALDEHYDE	50-00-0	0.26 %

**California Prop. 65**

WARNING: This product can expose you to chemicals including formaldehyde, 4-vinylcyclohexene, acrylonitrile, 1,3-butadiene, which is/are known to the State of California to cause cancer, and 4-vinylcyclohexene, 1,3-butadiene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**  
 TCSI : On the inventory, or in compliance with the inventory

	Page: 28
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

- TSCA : All substances listed as active on the TSCA inventory
- AIIC : On the inventory, or in compliance with the inventory
- DSL : All components of this product are on the Canadian DSL
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- NZIoC : Not in compliance with the inventory


**Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)


---

**SECTION 16. OTHER INFORMATION**


**Further information**

	Page: 29
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
	SDS Number: R0171291
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	Version: 3.0

**NFPA 704:**



**HMIS® IV:**




HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of H-Statements**

- H225 Highly flammable liquid and vapor.
- H227 Combustible liquid.
- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H350 May cause cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

**Full text of other abbreviations**

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -


 <b>BOSTIK</b>	Page: 30
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

This sds has been prepared by Bostik. (<http://www.Bostik.com>)

Sources of key data used to compile the Safety Data Sheet : Bostik internal data including own and sponsored test reports  
European Union Law with content from the Official Journal of the European Union.  
European Chemicals Agency; the EU authority implementing the EU's chemicals legislation for companies.  
The German Water Hazard Classes.  
ReachCentrum; a series of support services to help comply with REACH regulations.  
The European Commission; proposing legislation, administering and implementing EU policies, and enforcing EU law.  
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.  
Cefic, the European Chemical Industry Council.  
ESIS European Chemical Substances Information System

Revision Date : 03/04/2022

 <b>BOSTIK</b>	Page: 31
<b>SAFETY DATA SHEET</b>	Revision Date: 03/04/2022
	Print Date: 12/6/2023
Pliobond™ HT30 ADHESIVE ™ Trademark, Bostik or its subsidiaries, registered in various countries 133703	SDS Number: R0171291 Version: 3.0

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN